

[illegible]

AREA 640 ACRES
LOCATE WELL CORRECTLY

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). **SUBMIT IN TRIPlicate. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.**

WELL RECORD

George Turner, 417 1st. Nat'l Bnk. Bldg., El Paso, Texas.
Company or Operator Address
Wills Well No. 13 in NE 1/4 NW 1/4 of Sec. 13, T. 20S
Lease
R. 28 E, N. M. P. M., Russell Field, Eddy County.
Well is 331.7 feet south of the North line and 2339.6 feet ~~west of the west line~~ east of the west line of Sec. 13.
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is Address
If Government land the permittee is Neil H. Wills Address Carlsbad, N. M.
The Lessee is Dr. George Turner, 1st. Nat'l. Bldg, Address El Paso, Texas.
Drilling commenced June 2 19 46 Drilling was completed June 19, 19 46
Name of drilling contractor J. M. Cribbs & H. P. Keller Address Carlsbad, N. M.
Elevation above sea level at top of casing 3256 ? feet.
The information given is to be kept confidential until Sept. 1 19 46.

OIL SANDS OR ZONES

No. 1, from 808 to 845 No. 4, from _____ to _____
No. 2, from _____ to _____ No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from	49	to	85	feet.	36
No. 2, from	175	to	215	feet.	40
No. 3, from	236	to	297	feet.	61
No. 4, from	303	to	320	feet.	17

CASING RECORD

[illegible]

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10"	8 ⁵ / ₈	354'	None			run into mud filled hole.
8"	7"	745'	100	Halliburton		

PLUGS AND ADAPTERS

Heaving plug—Material None Length _____ Depth Set _____
Adapters—Material None Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
2 1/8"	Tin	Solidified	50 qts	6-19-46	745	745

Results of shooting or chemical treatment The hole cleaned itself and flowed by
heads at forty-five minute intervals after the shot.

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from None feet to _____ feet, and from _____ feet to _____ feet

Cable tools were used from 0 feet to 847 feet, and from _____ feet to _____ feet

PRODUCTION

Put to producing June 22, 1946
The production of the first 24 hours was 50 barrels of fluid of which 100 % was oil; _____ %
emulsion; _____ % water; and 0.2 % sediment. Gravity, Be 36.5
If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____
Rock pressure, lbs. per sq. in. _____

EMPLOYEES

J. M. Cribbs, Driller _____, Driller
H.P. Keller, Driller _____, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 22nd El Paso, Texas June 22, 1946
Place Date

day of June, 1946

Beaie Kassel
Notary Public

My Commission expires June 1, 1947

Name George Turner

Position	Owner
----------	--------------

Representing George Turner
Company or Operator

Address 417 1st Natl Bank Bldg.
El Paso, Texas

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	15	15	Caliche
15	49	34	Red Bed
49	85	36	Red sand (Water)
85	175	90	Red bed
175	215	40	Sand (Water)
215	236	21	Red bed
236	297	61	Sand (Water)
297	303	6	Red Bed
303	320	17	Sand (Water)
320	335	15	Red shale
335	350	15	Sand (Water)
350	354	4	Red bed
354	390	36	Red shale
390	465	75	Red bed.
465	613	148	Salt
613	682	69	Anhy
682	705	23	Red bed
705	725	20	Anhy
725	745	20	Lime
745	790	45	Gray lime
790	795	5	Lime & Anhy
795	802	7	Hard lime (white)
802	808	6	Broken sandy lime
808	819	11	Sandy shale (Blue) (Oil show)
819	831	12	Sand and shale (Oil show)
831	845	14	Sand (oil)
845	847	2	Hard lime.

50-015-02584

ORRID 153653

PROP 18882

POOI 52820