

N

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

AREA 640 ACRES  
LOCATE WELL CORRECTLY

A. W. Rutter Hotel Paso del Norte El Paso, Texas  
Company or Operator  
Ohio Oil Co. State Well No. 1 in SE 1/4 SE 1/4 of Sec. 21, T. 20  
Lease  
R. 28 N. M. P. M. Wildcat Field, Eddy County.  
Well is 990 feet North of the South line and 990 feet west of the East line of Sec 21  
If State land the oil and gas lease is No. 8958 Assignment No.  
If patented land the owner is Address  
If Government land the permittee is Address  
The Lessee is Ohio Oil Company Address Houston, Texas  
Drilling commenced December 30, 1945 Drilling was completed Jan. 9, 1946  
Name of drilling contractor W-W Drilling Co. Address Carlsbad, New Mexico  
Elevation above sea level at top of casing 3248 feet.  
The information given is to be kept confidential until Not Confidential 19

## OIL SANDS OR ZONES

No. 1, from 721 to 750 Gas Sand No. 4, from to  
No. 2, from to No. 5, from to  
No. 3, from to No. 6, from to

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from No water to feet.  
No. 2, from to feet.  
No. 3, from to feet.  
No. 4, from to feet.

## CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
7"	17#	8	BSW	616 Tex	Type				

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
8 3/4"	7"	616	25	Halliburton		

## PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set  
Adapters—Material Size

## RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet  
Cable tools were used from feet to feet, and from feet to feet

## PRODUCTION

Put to producing Not Producing 19  
The production of the first 24 hours was barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be  
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas  
Rock pressure, lbs. per sq. in.

## EMPLOYEES

Driller Driller  
Driller Driller

## FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this Place Date

Name

## FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
1	94	94	Red Bed
94	165	71	Red Bed
165	216	51	Anhydrite & Red Bed
216	340	124	Sand Potash & Salt
340	405	65	Salt Anhydrite
405	470	65	Salt Anhydrite
470	505	35	Anhydrite & Lime
505	530	25	Anhydrite & Lime
530	540	10	Anhydrite & Lime
540	560	20	Anhydrite
560	570	10	Grey Lime
570	575	5	Brown Lime
575	595	20	Lime & Anhydrite
595	615	20	Anhydrite
615	616	1	Brown Lime
616	623	7	Lime
623	625	2	Grey Lime
625	638	13	Grey Lime
638	650	12	Anhydrite
650	653	3	Anhydrite
653	662	11	Grey Lime
662	675	13	Sand Anhydrite
675	680	5	Lime
680	688	8	Anhydrite
688	690	2	
690	695	5	Anhydrite
695	700	5	Anhydrite
700	705	5	Grey Lime
705	710	Grey Lime	
710	715	5	Brown Lime
715	730	15	Lime & Sand (gas at 7218)
730	752	22	Sand
752	754	2	Lime (Total Depth)