Box 1545 Hobbs, New Mexico October 7, 1949

Mr. Leo Schutz State Land Office Santa Fe, New Mexico

Dear Leo:

As per your request of September 27, 1949, I have again visited the Mappier gas well and have the following report:

Total depth hole 833 feet, had 3 1/2 balers of water from 830 to 833, per hr. put in a four footbridge of rock, tampered down with tools, then put 100 lbs of lead wool on top of the rock bridge, and then drove it down, let it set 12 hours, baled water off, then let set 2 hours, and found no water in hole, then dumped 6 sacks of cement on top of lead wool, let set 24 hours, then run baler, and found no water in hole, the cement and lead wool with the rock bridge plugged to hole back to 790 fest, then shot the well, put in 6 feet of gravel on top of the cement for a cushion for the shot, then when cleaned out after the shot we drove the tin containers down to 780 feet, this is the bottom of the hole as plugged back. 10 inch casing pulled, 8 inch and 7 inch cemented together to the top of the hole. (Information from Form C-105 upon completion of the well)

The test I made is as follows:

After blowing wide open through 2" for 45 minutes, well was delivering gas at rate of 2,310,000 cu. ftt per day.

Very truly yours,

ROY log

,

10 1974 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 19 2019 € 1 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 19

1000 M.

a source conservations of the second of t A second of the second of the

1 as in the basis of the set, for the basis of the set of the

and the second of the second set

LATER OF BUT STOR

C : 1