



AREA 640 ACRES  
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

Dr. George Turner 417 1st. Nat'l Bldg. Bldg. El Paso, Texas  
Company or Operator Address  
State B-9775 Well No. 1 in SE 1/4 SW 1/4 of Sec. 21, T. 20S  
Lease  
R. 28E, N. M. P. M., Wildcat Field, Eddy County.  
Well is 231.0 feet south of the North line and 990 feet east of the west line of Sec. 21, 20S, 28E.  
If State land the oil and gas lease is No. B-9775 Assignment No. 5.  
If patented land the owner is Address  
If Government land the permittee is Address  
The Lessee is George Turner Address 417 1st. Nat'l Bldg. Bldg. El Paso, Texas  
Drilling commenced Oct. 4 1946. Drilling was completed Oct. 25 1946  
Name of drilling contractor J. M. Cribbs Address Carlsbad, New Mexico  
Elevation above sea level at top of casing 3240 feet.  
The information given is to be kept confidential until December 1 1946.

OIL SANDS OR ZONES

No. 1, from 784 to 805 (Dry) No. 4, from to  
No. 2, from 813 to 821 (Dry) No. 5, from to  
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.  
No. 1, from 35 to 75 feet. 40 Water rose to within  
No. 2, from to feet. approximately 25' of the  
No. 3, from to feet. surface. It was not  
No. 4, from to feet. bailed down.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
8 5/8"	28 lb.	8	T&C	200'	O.D.	None	No	No	Shut off water
7"	20	8	H-40	647'	O.D.	None	No	No	Oil string

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
10"	8 5/8"	200'	None	None	Landed in mud	filled hole
8"	7"	647'	50	Halliburton	None	None

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set  
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
None	None	None	None	None	None	None

Results of shooting or chemical treatment Not shot

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from none feet to none feet, and from feet to feet  
Cable tools were used from 0 feet to 864 feet, and from feet to feet

PRODUCTION

Put to producing Dry, 19  
The production of the first 24 hours was none barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be  
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas  
Rock pressure, lbs. per sq. in.

EMPLOYEES

J. M. Cribbs, Driller  
S. Sloan, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this Place Date  
Name

# FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	3	3	Sand
3	8	5	Caliche
8	18	10	Shale
18	35	17	Red bed
35	75	40	Sand (Water)
75	110	35	Shale
110	160	50	Shale & shells
160	180	20	Green shale
180	300	120	Red bed
300	375	75	Gypsum
375	412	37	Salt
412	740	328	Anhy.
740	749	9	Gray lime
749	754	5	Brown Lime
754	759	5	Gray lime
759	764	5	Dark lime
764	774	10	Hard grayish-white lime
774	779	5	Gray sandy lime
779	784	5	Gray lime
784	805	21	Sand (Dry)
805	813	8	Gray lime
813	821	8	Sand (Dry)
821	831	10	Blue shale & lime (Water show)
831	845	14	Gray lime
845	855	10	Brown sandy lime
855-	863	8	Gray lime
863	864	1	Sulfur water