Form 9-330
(Rev. 5-63)

NM OIL CONS. COMMISSION
Drawer DD
Artesia, NM 88210

RECEIVED BY
AUG 03 1984
ARTESIA, OFFICE

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE (See other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R355.5.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☐ DRY ☐ Other

JUN 8 1983
OIL & GAS
ROSWELL, NEW MEXICO

b. TYPE OF COMPLETION: NEW WELL ☐ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ Other

2. NAME OF OPERATOR: Exxon Corporation

3. ADDRESS OF OPERATOR: Post Office Box 1600, Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*
At surface: 1980' FNL and 1980' FWL of Section
At top prod. interval reported below
At total depth

5. LEASE DESIGNATION AND SERIAL NO.: NM-01119
6. IF INDIAN, ALLOTTEE OR TRIBE NAME: ---
7. UNIT AGREEMENT NAME: ---
8. FARM OR LEASE NAME: Yates Federal C
9. WELL NO.: 6
10. FIELD AND POOL, OR WILDCAT: Avalon-Delaware
11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA: Section 31, T20S, R28E
12. COUNTY OR PARISH: Eddy
13. STATE: New Mexico
14. PERMIT NO.: [redacted]
DATE ISSUED: 11/18/82

15. DATE SPUDDED	16. DATE T.D. REACHED	17. DATE COMPL. (Ready to prod.)	18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*	19. ELEV. CASINGHEAD
1/06/83	1/16/83	2/20/83	KB 3260	

20. TOTAL DEPTH, MD & TVD	21. PLUG, BACK T.D., MD & TVD	22. IF MULTIPLE COMPL., HOW MANY*	23. INTERVALS DRILLED BY	ROTARY TOOLS	CABLE TOOLS
4700'	3865'	--	→	0-4700'	

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*
Delaware Sand 3550-3624'

25. WAS DIRECTIONAL SURVEY MADE: No

26. TYPE ELECTRIC AND OTHER LOGS RUN: DLL-GR; EPT; FDL

27. WAS WELL CORED: Yes

BUREAU OF LAND MGMT.
RECEIVED
ROSWELL, DIST.

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24#	634'	12 1/4"	325 sx Lite; 175 sx Cl C	
5 1/2"	14#	4699'	7 7/8"	950 sx Cl C	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)
None				

30. TUBING RECORD

SIZE	DEPTH SET (MD)	PACKER SET (MD)
2 7/8"	4464'	

31. PERFORATION RECORD (Interval, size and number)
3950-3970 w/21 shots
3550-3595 w/24 shots
3606-3624 w/19 shots

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
3950-3970	Acdz w/1500 gal 15% HCl
CIBP @ 3900'	Cap w/35' cement
3550-3624	Acdz w/4500 gal HCl

33.* PRODUCTION

DATE FIRST PRODUCTION	PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)	WELL STATUS (Producing or shut-in)
2/20/83	Flowing	Producing

DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
5/14/83	24.0	27/64"	→	123	393	167	2,374

FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)
420		→				42

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.): Flared

TEST WITNESSED BY

ACCEPTED FOR RECORD
JUL 12 1983
ROSWELL, NEW MEXICO

35. LIST OF ATTACHMENTS

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED Melba Knipling TITLE Unit Head DATE May 25, 1983
Melba Knipling

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.
If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.
Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.
Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.
Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.
Item 29: *"Sacks Cement":* Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.
Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES:
SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.
Delaware Sand	2508'		Sandstone and Shale
			Cores: 2563-2584' 2584-2644' 3598-3658'

38. GEOLOGIC MARKERS

NAME	TOP MEAS. DEPTH	TOP TRUE VERT. DEPTH
Delaware	2508'	