Form 9-331 a (Feb. 1951)						
		. 	·			

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

and Office Sente 38
ease No
nit

1 0 1956

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	 SUBSEQUENT REPORT OF WATER SHUT-OFF SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING SUBSEQUENT REPORT OF ALTERING CASING SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR SUBSEQUENT REPORT OF ABANDONMENT SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO SHOOT OF ALTER CASING	 SUPPLEMENTARY WELL HISTORY

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

s .			July	13	
Conley Well No. 1 is local	ted 1 650 ft.	from $\left\{ \begin{array}{l} \mathbf{X} \mathbf{N} \\ \mathbf{S} \end{array} \right\}$ line	and 2310. ft	from $\{E\}$ line	of sec. 33
SE Section 33	20S (Twp.)	(Range)	(Meridia	n)	
Undesignated (Field)	: C	ounty or Subdivision)		(State or Territor	у)

The elevation of the derrick floor above sea level is 31 22.6 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is planned to drill an o 3/4" Rotary sole to a depth of approximately 100' where 7" cag. will be set to shut off surface water expected at about 75-80'. of hole will then be drilled to the top of the Yates formation, expected at about 520'. It this point 53" cag will be run and yates will be crilled either with oil, or with cable tools. If well is producer, 52" cag will be cemented with 50 sacks. If hole is dry, all possible casing will be pulled and well will be plugged in accordance with USSS regulations.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be contained.

Company George S. Conlay	L)
Address Sox 611	
Sente re, ne rexise	Ву
	Title operator