

Santa Fe, New Mexico E C F

DEC 2 1964

□.
ARTEBIA, Ur. 12

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

Neil E. Salsich

.....
(Company or Operator)

Malco NAM

(L-250)

Well No. 1-X in SW $\frac{1}{4}$ of NW $\frac{1}{4}$, of Sec. 33, T. 20S, R. 10E, NMPM.

Saladar Yates

Pool.

Eddy

County

Well is 2310 feet from North line and 985 feet from West line

of Section 33 If State Land the Oil and Gas Lease No. is.....

Drilling Commenced 5/3/57 19..... Drilling was Completed 5/15/57 19.....

Name of Drilling Contractor..... W & W Drilling Company.....

Address..... Carlsbad, New Mexico.....

Elevation above sea level at Top of Tubing Head.....3202..... The information given is to be kept confidential until
~~now~~..... 19.....

No. 1, from.....to..... No. 4, from.....to.....

No. 2, from to No. 5, from to

No. 3, from.....to..... No. 6, from.....to.....

No. 3, from.....to..... No. 6, from.....to.....

No. 3, from.....to..... No. 6, from.....to.....

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....

No. 2, from to feet.

No. 3, from.....to.....feet.....

No. 4, from _____ to _____ feet.

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
7 ⁿ	20 [#]	new	223				surface
4 ¹ / ₂	9.5	new	719	Baker	240'	692-704	production

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
9 5/8	7	223	none	mudded		
6 1/4	4 1/2	719	75	pumped		

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

perforated 4 1/2" casing from 692-704 with 4 shots per foot, washed perfs with 250 gals mud acid sand-oil fraced with 10,000 gals oil and 20,000# sand

Result of Production Stimulation.....plugged and abandoned

Depth Cleaned Out.....

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 726 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing, 19

OIL WELL: The production during the first 24 hours was barrels of liquid of which % was
was oil; % was emulsion; % water; and % was sediment. A.P.I.
Gravity

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy. 210	T. Devonian	T. Ojo Alamo
T. Salt	T. Silurian	T. Kirtland-Fruitland
B. Salt. 470	T. Montoya	T. Farmington
T. Yates. 675	T. Simpson	T. Pictured Cliffs
T. 7 Rivers	T. McKee	T. Menefee
T. Queen	T. Ellenburger	T. Point Lookout
T. Grayburg	T. Gr. Wash	T. Mancos
T. San Andres	T. Granite	T. Dakota
T. Glorieta	T.	T. Morrison
T. Drinkard	T.	T. Penn
T. Tubbs	T.	T.
T. Abo	T.	T.
T. Penn	T.	T.
T. Miss	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	210	210	red beds				
210	470	260	anhy & salt				
470	675	205	red beds & anhy				
675	726	51	sand				

OIL CONSERVATION COMMISSION
ARIZONA DISTRICT OFFICE
No. Copies Preserved
DISTRIBUTION
FOR
GRANITE
SANTA FE
PRODUCTION OFFICE
STATE LAND OFFICE
U. S. G. S.
TRANSPORTER
FILE
BUREAU OF MINES

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far
as can be determined from available records.

Company or Operator Neil E. Salsich
Name John Hottel Reed

12/21/59 (Date)
Address 716 1st Nat'l. Bank Bldg. - Midland, Tex
Position or Title Geologist