

Drilling Bond for the George Etz et al No. 1
State (application attached) will be carried
under the blanket bond of \$10,000.00 , alraedy
of record with Grant Keyes and George Etz as
personal sureities.

George Etz
.....
George Etz, operator

Drilling Bond for the George Eitz et al No. 1
State (application attached) will be carried
under the blanket bond of \$10,000.00 , already
of record with Grant Keyes and George Eitz as
personal sureties.

.....
George Eitz, operator

EW MEXICO STATE LAND OFFICE


Santa Fe, New Mexico

DEPARTMENT OF THE STATE GEOLOGIST
NOTICE OF INTENTION TO DRILL NEW WELL

Notice must be given to the State Geologist or to the proper Oil and Gas Inspector and approval obtained before drilling begins. If changes in the proposed plan are considered advisable a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval.

Mr. F. J. Vesely, State Geologist. Roswell N. Mex., Mar. 28 1935

Dear Sir: You are hereby notified that it is our intention to commence the drilling of a well to be known as George Etz et al Well No. 1 in NE 1/4 of Sec. 36 T. 20 S., R. 28 E., N. M. P. M., Avalon Oil Field Eddy County



The well is 660 feet (X) of N line and 1980 feet (E.)

W of W line of Section 36

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. 3-2451
Assignment No. 1

If patented land the owner is _____

Address _____

The lessee is George Etz Address Roswell, New Mexico

The elevation of the derrick floor above sea level is _____ feet. We propose to drill well with No. 2 National

Make of Drill _____

We propose to use the following strings of casing and to land or cement them as indicated.

Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented
10"		Second hand	about 100'	landed
8 1/4"		"	about 350'	landed
6 5/8"		New	about 900'	cemented

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 1000' feet.

Additional information:

**10" casing will be run to shut off surface waters and mudded to surface.
8 1/4" casing will be run if necessary to shut off additional waters found
or to protect the hole from caving. Little or no salt is expected but
this will be protected by the 6" string if production is found by cementing the 6" string.**

Sincerely yours,

Approved APR 1 1935, 19_____
Except as follows:

George Etz et al
Company or Operator.

By George Etz
Position Operator

Send communication regarding well to

Name Neil H. Willis

Address Roswell, New Mexico

State Geologist or Oil and Gas Inspector.

F. J. Vesely