
(SUBMIT IN TRIPLICATE)



## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land	Offi	. Las	Cruces
Loaso	No.	07006	61
Unit .		M	

ACTING DISLUNDRY NOTICES AND REPORTS ON WELLS

NOTIC			
10110	E OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
INOTIC	E OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.	
NOTIC	E OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING	
NOTIC	E OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF ALTERING CASING SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
MOTICI	E OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR SUBSEQUENT REPORT OF ABANDONMENT	
NOTIC	E OF INTENTION TO PULL OR ALI'ER CASING	SUPPLEMENTARY WELL HISTORY	A.
	E OF INTENTION TO ABANDON WELL		
	(INCICATE ABOVE BY CHECK MARK	NATURE OF REPORT, NOTICE, OR OTHER DATA)	
		August 24	
Well No.	½ Sec. and Sec. No.) 21 South 28 (Twp.)	S line and 660 ft. from W line of sec.	.33
	(Field) Eddy (County or	Subdivision)  New Mexico (State or Territory)	
The ele	vation of the derrick floor above sea leve	(State or Territory)	
	TOTAL HOOF ADOVE SEX 1646	1 183142_ ft.	
State nam	DETAIL les of and expected depths to objective sands; show sizes.	S OF WORK  weights, and lengths of proposed casings; indicate mudding job er important proposed work)	
4-61	plug set at 2 700% 300%	pump truck using 32 drill pipe. 100	
	at 565°, 20° coment plug set a	t the top with 4" marker.	ug se
<b>⊢</b> 61	at 565°, 20° coment plug set a Cleaned up location.	t the top with 4" marker.	ug se
<b>⊢</b> 61	at 565%, 20% coment plug set a	t the top with 4" marker.	emiliug se
<b>⊱6</b> 1	at 565%, 20% coment plug set a	t the top with 4" marker.	ug se
<b>⊢</b> 61	at 565%, 20% coment plug set a	t the top with 4" marker.	ug se
- <b>-</b>	at 565*, 20* cement plug set a Cleaned up location.	t the top with 4" marker.	ug se
- <b>-</b>	at 565*, 20* cement plug set a Cleaned up location.	t the top with 4" marker.	ug se
I underst:	at 565°, 20° cement plug set a Cleaned up location.	t the top with 4" marker.	ug se
mpany	at 565°, 20° cement plug set a Cleaned up location.  and that this plan of work must receive approved in write Ralph Nix and Jerry Curtis	t the top with 4" marker.  Au 36  Ing by the Geological Survey before operations may be commented.	ug se
I understa	at 565°, 20° cement plug set a Cleaned up location.	t the top with 4" marker.  Au 36  Ing by the Geological Survey before operations may be commented.	ug se
I understa	at 565°, 20° cement plug set a Cleaned up location.  and that this plan of work must receive approved in write Ralph Nix and Jerry Curtis	t the top with 4" marker.  Au 36  Ing by the Geological Survey before operations may be commented.	ug se