

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office San Antonio

Case No. 047042

Well No. 1

SUNDRY NOTICES AND REPORTS ON WELLS

| | | |
|---|---|---|
| NOTICE OF INTENTION TO DRILL..... | SUBSEQUENT REPORT OF WATER SHUT-OFF..... | |
| NOTICE OF INTENTION TO CHANGE PLANS..... | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... | |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF..... | SUBSEQUENT REPORT OF ALTERING CASING..... | |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL..... | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR..... | |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE..... | SUBSEQUENT REPORT OF ABANDONMENT..... | X |
| NOTICE OF INTENTION TO PULL OR ALTER CASING..... | SUPPLEMENTARY WELL HISTORY..... | |
| NOTICE OF INTENTION TO ABANDON WELL..... | | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

August 22, 1948

Well No. 1 is located 1652 ft. from SEC. 1 line and 2328 ft. from E line of sec. 1

SE 1/4 Sec. 1 T. 20 S. R. 12 E. N. M. P. M.

Wildcat
(Field)

Kady
(County or Sub-division)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show plug, weights, and lengths of proposed casings; indicate reworking jobs, cementing points, and all other important proposed work)

The well was plugged as follows:
Hole was plugged back from 1800' to 1785' with rock and 325' lead wool was driven above the rock plug to 1782'. Hole was bailed dry, and a 10 sack cement plug was placed from 1782' to 1785'. Hole was then filled with rotary mud to 1570' and 7" casing, set at 1560', was pulled. A 10 sack cement plug was placed in 8-5/4" hole from 1370' to 1340'. Hole was then filled with mud to 360', where 10 sack cement plug was placed from 360' to 350' up into 8" casing. The 8-5/8" casing was then knocked off and 225' was salvaged. The hole was then filled with mud to the surface and 4" pipe erected and cemented with 5 sacks as a marker. Grounds were cleared and leveled off.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Nail H. Mills

Address Box 522

Carlsbad, New Mexico

By

Title operator