

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN PLIC
(Other instructions
verse side)

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR SEKILLY OIL COMPANY	8. FARM OR LEASE NAME E. C. RANDON
3. ADDRESS OF OPERATOR P.O. BOX 730, MOSSES, NEW MEXICO	9. WELL NO. 3
4. LOCATION OF WELL (Report location clearly and in accordance with any applicable requirements. See also space 17 below.) At surface 600' FWL & 1540' FWL SECTION 13, T 20 S, R 29 E	10. FIELD AND POOL, OR WILDCAT ARTESIA
14. PERMIT NO. H. C. RANDON	11. SEC. T. R. M. OR BLM. AND SURVEY OR AREA SECTION 13, T 20 S, R 29 E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3331 GR.	12. COUNTY OR PARISH ELKI
	13. STATE New Mexico

RECEIVED

NOV 16 1965

O. C. C.
ARTESIA, OFFICE

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☒	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	(Other) ☐
(NOTE: Report results of multiple completion on Well Completion or Recombination Report and Log form.)			

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and senses pertinent to this work.)*

Casing presently in well: T.D. 1397'
8 1/4" Casing @ 1353' (Landed with no cement.)
10 3/4" Casing @ 1075' with 20 Sacks
12 1/2" Casing @ 343' with 125 Sacks

Move in hydraulic casing puller, out and pull all casing possible.

Spot 100' salt water cement plug 1397' T.D.

Spot solid salt water cement plug from 1175' back to surface.

Install regulation 4" pipe marker.

(NOTE: If unable to pull casing through potash interval, will isolate potash zone by perforating at approximately 700' and circulating salt water cement back to surface.)

Instructions as per telephone conversation with Mr. James A. Kasuf, District Engineer with U.S.G.S.

18. I hereby certify that the foregoing is true and correct

SIGNED

(This space for Federal or State office use)

TITLE **DISTRICT SUPERINTENDENT**DATE **Oct. 19, 1965**

APPROVED BY

CONDITIONS OF APPROVAL IF ANY:

TITLE

DATE

NOTIFY USGS IN SUFFICIENT TIME TO

WITNESS CEMENTING THE

*See Instructions on Reverse Side

RECEIVED
NOV 15 1965
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO
RUDOLPH C. [Signature]
ACTING DISTRICT ENGINEER

WSE/LMR/bh

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State law. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and gate well conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-385229
6-67-881

Nov. 16, 1955

The attached form probably shows Geo. F. Getty
Oil Company as the operator in 13-205-29E.

Geo. F. Getty

FORMATION RECORD-Continued

FROM	TO	TOTAL FEET	FORMATION
0	35	35	Gyp
35	120	85	Red rock
120	137	17	Gyp
137	140	3	Gravel, dry
140	145	5	Gyp
145	160	15	Sand and gravel
160	170	10	Gyp and red bed
170	180	10	Sand and gravel
180	195	15	Gyp and red rock
195	220	25	Sandy red bed and gray shale
220	252	32	Gray shale
252	258	6	Sandy gray shale
258	273	15	Red bed
273	280	7	Red beds sandy
280	290	10	Sand
290	300	10	Red bed and gray shale
300	320	20	Sandy red bed
320	330	10	Red bed and blue shale
330	345	15	Red bed T. S.
345	490	145	Pink salt
490	500	10	Gyp
500	890	390	White and pink salt
890	900	10	Salt and gyp
900	1045	145	Salt
1045	1070	25	Anhydrite
1070	1080	10	Lime and anhydrite
1080	1100	20	Dark gray lime
1100	1120	20	Hard brown lime
1120	1170	50	Dark gray lime
1170	1190	20	Light gray lime
1190	1210	20	Brownish lime
1210	1250	40	Hard gray lime
1250	1270	20	Light gray lime
1270	1290	20	Brown and gray lime
1290	1396	106	Light gray lime
1396	1397	1	Lime - OIE

T. D. 12

LOG OF OIL OR GAS WELL

COMPANY AMERICAN F. Getty Oil Co Address 1060 Subway Terminal Bldg. Los Angeles, Cal.
 Name of Trust H. C. Rawson Field Getty South State New Mexico
 Well No. 3 Sec. 13 T. 20 R. 29 Meridian N M P. M. County Eddy
 Location 1/4 Sec. 13 of S. 1 Line and 1/4 Sec. 13 of N Line of Sec. 13 Elevation 3331'
 (Sketch show section to well level)

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Signed C. M. Hall

Date Sept. 20, 1928

Title Superintendent

The summary on this page is for the condition of the well at above date.

Commenced drilling 7-23-28, 1928 Finished drilling 9-13-28, 1928

OIL OR GAS SANDS OR ZONES

(Denote gas by G)

No. 1, from 1396 to 1397 Oil & Gas No. 4, from to
 No. 2, from to No. 5, from to
 No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

No. 1, from 145 to 160 No. 3, from 280 to 290
 No. 2, from 170 to 180 No. 4, from to

FOOT DRILLING RECORD

Time	Weight	Depth per	FO Meters	Amount	Kind of shoe	One end pulled from	100' Estimated	Purpose
10 ⁰⁰	100	10	1075'	DBX	Plain	over well		Protect salt
11 ⁰⁰	100	10	1353'	DBX	Plain			Protection
								drilling

MUDDING AND CEMENTING RECORD

Time	Weight	Amount of cement	Method used	Mud grade	Amount of mud used
11 ⁰⁰	100	195 lbs	Haliburton		
12 ⁰⁰	100	250	Dump Bailor		
		250			
		250			
		250			
		250			

PLUGS AND ADAPTERS

Heaving Material Length Depth set
 Adapters Material Size

SHOOTING RECORD

Time	Shot used	Register used	Quantity	Date	Depth shot	Depth charged out
10 ⁰⁰	100					
11 ⁰⁰	100					
12 ⁰⁰	100					
13 ⁰⁰	100					
14 ⁰⁰	100					
15 ⁰⁰	100					

TOOLS USED

Rotary used from feet to feet
 Cuts used from feet to 1397 feet, and from feet to feet

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

U.S. Land Office Las Cruces

Serial Number 08840

Inspector G. Rawson

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	☒	SUBSEQUENT RECORD OF SHOOTING	
NOTICE OF INTENTION TO CHANGE PLANS		RECORD OF PERFORATING CASING	
NOTICE OF DATE FOR TEST OF WATER SHUT-OFF		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
REPORT ON RESULT OF TEST OF WATER SHUT-OFF		NOTICE OF INTENTION TO ABANDON WELL	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO SHOOT		SUPPLEMENTARY WELL HISTORY	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 13, 1928, 192

Following is a notice of intention to do work on land under permit described as follows:

New Mexico Eddy Artesia Field, South
(State or Territory) (County or Subdivision) (Toll)
Well No. 1 Sec. 13 20 S. 29 E. N.M.P.M.
(1 Sec. and Sec. No.) (Twp.) (Range) (Section)

The well is located 660 ft. N of S. line and 154 ft. E of W. line of sec. 13

The elevation of the derrick floor above sea level is 3331 ft.

DETAILS OF PLAN OF WORK

(State purpose of and expected depths to objective sands; show dips, weights, and lengths of proposed casings; indicate mudlogging jobs, estimating points, and all other important proposed work.)

Intend to drill well to about 2000', unless oil or gas is found in commercial quantities at a lesser depth. Production is expected between 1350 and 1400'. Will set about 200' of 12" hole, 50' casing, below all surface waters and cement with 10 sacks cement.

Intend to drill through the salt with 12" hole and reduce hole to 10" below the salt. Drill to about 1300', reduce hole to 8" and drill into oil horizon. If oil and gas are found in commercial quantities, 10" will be set below the salt and 8" at about 1300'. If commercial oil is found and no gas encountered, will ream 12" hole to about 1300' and set 10" casing at this point.

Approved (SEE ATTACHED) July 17, 1928

Company GEORGE F. GETTY OIL CO.

By J. M. Wallace

Title Permit Supervisor

Title Geologist

Address Casper, Wyoming

Provisionally approved 7/12/28 by J.M.