

APPROVED

DEC 14 1962
Orig. Sign. RONNIE E. SHOOK
RONNIE E. SHOOK
ACTING DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office _____
Lease No. 029133
Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	Report of Setting & Cementing Casing
	Subsequent Report of Treating Well

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

(Frac)

December 12, 1962

Texaco Federal
Well No. 2 is located 1470 ft. from [N] line and 1170 ft. from [W] line of sec. 13
SW/4 of NW/4 Sec. 13 20S 29E 10W
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Cetty Eddy New Mexico
(Field) (County or Subdivision) (State or Territory)

RECEIVED

DEC 17 1962

The elevation of the derrick floor above sea level is 3320 ft.

DETAILS OF WORK

D. C. C.
ARTESIA, OFFICE

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Set 334' 8-5/8" Casing cemented w/100 sz Heat Cement, Circulated to surface
Set 1350' 5-1/2" casing, cemented w/25 sz Heat cement.
Drill to 1445 TD
PB 1395'
Acidize with 6,000 gallons acid
Frac w/20,000 Gal 3% acid plus 20,000# sand
Pump back load water & run potential test.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company PAUL E. JACKINS
Address 2007 Wilco Bldg.
Midland, Texas

By M. F. Fuson
Title Production