

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYU. S. G. C. COPY  
SUBMIT INSTRUCTIONS  
(Other side)  
copy toForm Approved  
Budget Bureau No. 42 F112  
CLASS DESIGNATION AND SYMBOL NO.

NM-0397642

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR PAUL E. MASKINS ✓	8. FARM OR LEASE NAME TEXACO-FEDERAL
3. ADDRESS OF OPERATOR P.O. BOX 4621, MIDLAND, TEXAS 79701	9. WELL NO. 2
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1,470' FROM NL 1,170' FROM <del>Q</del> OF SEC. 13, T-20S, R-29-E WL	10. FIELD AND POOL, OR WILDCAT GETTY
14. PERMIT NO.	11. SEC., T., R., M., OR SLS. AND SURVEY OR AREA S-13 T-20S, R-29E
15. ELEVATIONS (Show whether DF, ST, OR, etc.) 3,320' DF	12. COUNTY OR PARISH 13. STATE

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

255'  
SET ~~250'~~ PLUG FROM 1,190' TO 1,445', T.D. W/25 SX.  
SET ~~250'~~ PLUG FROM ~~450'~~ TO ~~350'~~ W/25 SX. 120  
SET 350' PLUG FROM 350' TO SURFACE W/25 SX.  
20'

8-5/8" CASING WAS SET @ 334', CEMENTED TO SURFACE

5-1/2" CASING WAS SET @ 1,350', CEMENTED W/25 SX.

1" TUBING RUN TO 1,100' (TOP CEMENT) &amp; CEMENTED TO SURFACE.

ALL CASING WILL BE LEFT IN HOLE

MARKER WILL BE PLACED IN TOP. PLUG LOCATION CLEANED.

3 plugs  
Note depth and  
casing cement  
each plug

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE OPERATOR

DATE 8/1/67

(This space for use by operator or owner, as applicable)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

AUG 1 1967  
R. L. CULPIN  
ACTING DISTRICT ENGINEER

NOTIFY US IN SUFFICIENT TIME TO

WITHIN OF

\*See Instructions on Reverse Side