

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN
(Other instru-
verse side)

LICATE
s of re-

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 029009 (a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Tidewater Oil Company	8. FARM OR LEASE NAME GO Geo. Dooley "A"
3. ADDRESS OF OPERATOR Box 249, Hobbs, New Mexico	9. WELL NO. 10
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FSL & 660' FWL, Sec. 24, 20S, 29E	10. FIELD AND POOL, OR WILDCAT Cotton
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 24, 20S, 29E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) DF 3312	12. COUNTY OR PARISH Edgy
	13. STATE N. Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

We propose to plug and abandon the GO Geo. Dooley "A" Well #10 in accordance with MBOCC Order E-11-A. This well is no longer economical to operate.

We intend to pull all casing strings at their lowest free point and lay a solid cement plug from TD to surface. In the event we are unable to pull casing opposite the salt section, we will run a cement bond log to determine cement coverage, then perforate and squeeze if necessary. Attached is a sketch showing all available down hole information.

RECEIVED

SEP 14 1965

U.S. GEOLOGICAL SURVEY

RECEIVED
SEP 13 1965
U.S. GEOLOGICAL SURVEY


18. I hereby certify that the foregoing is true and correct

SIGNED C.R. Wade

TITLE Area Supt.

DATE 9-10-65

(This space for Federal or State office use)



TITLE

DATE

NOTIFY USGS IN SUFFICIENT TIME TO

WITNESS all plugging operation

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

Dosley No. 10

Completion: 1-1-48

12½" 50# BV @ 212'
 (May have been pulled)

8⅝" 32# BV @ 409'
 Cement: 100 sks.

3" EUE @ 1359' →

6⅝" 20# BV @ 1340'
 Cement: 100 sks.

Water: 150-160'
 Top Salt: 370'
 Base Salt: 968'

RECEIVED
SEP 13 1965
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

RECEIVED

SEP 14 1965

D. C. C.
ARTESIA OFFICE

PBTD 1360'
 TD 1390'