

N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Just Use

Oil Co. Wells at 41, Box 589, Carlsbad, New Mexico
Company or Operator Address

Lease Well No. 7-0 in 15 of Sec. 15, T. 20 S.
R. 30 N. M. P. M. Field, County.

Well is 1650 feet south of the North line and 2970 feet west of the East line of Sec. 15

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Address

If Government land the permittee is Oil Co. Wells, Address Box 589, Carlsbad, N. M.

The Lessee is Leves, Address

Drilling commenced 10-13-47 19 Drilling was completed 11-17-47 19

Name of drilling contractor Drilling Co., Address Box 589, Carlsbad, N. M.

Elevation above sea level at top of casing 3210 feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 1532 ~~xxxx~~ to 1590 No. 4, from to
No. 2, from 1635 to 1685 No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
7"	20.7	8	J&L	1341	Per Int		490'		Top of salt and oil string.

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	7"	1531	100	Halliburton		at bottom
	7"	1531	100	Halliburton	490'	thru 2-stage tool

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 1341 feet, and from feet to feet
Cable tools were used from 1341 feet to 1635 feet, and from feet to feet

PRODUCTION

Put to producing 11-20-47 19
The production of the first 24 hours was 39* barrels of fluid of which 98.8% was oil; 1.2% emulsion; % water; and % sediment. Gravity, Be
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in. * 3 in. pump test.

EMPLOYEES

Driller J. L. Collins Driller
Driller J. L. Wilson Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 22nd

Carlsbad, New Mexico November 22, 1947

day of November 19 47

Name R. H. Wilson

Position Owner

Representing

Notary Public

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	3	3	Sand & Soil
3	7	4	Gypsum
7	46	39	Sandy Red Shale
46	255	209	Anhydrite
255	265	10	Red Shale
265	280	15	Soft White Lime
280	300	20	Gypsum and anhydrite
300	375	75	Red bed
375	460	85	Salt
460	470	10	Anhydrite
470	505	35	Salt and Red Clay
505	526	21	Lime
526	545	19	Red Shale
545	660	115	Salt & Shale
660	670	10	Anhydrite
670	703	33	Salt & Potash
703	935	232	Salt and Red Shale
935	950	15	Anhydrite
950	1160	210	Salt
1160	1165	5	Anhydrite
1165	1200	35	Salt
1200	1220	20	Salt
1220	1257	37	Anhydrite
1257	1535	278	Lime
1535	1543	8	Sandy Lime
1543	1596	53	Lime - Show oil 1592-96
1596	1633	37	Lime Increasing oil

Total Depth 1633'