

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	X
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

Carlsbad, New Mexico

February 17, 1954

Place

Date

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the Neil H. Wills

State Well No. 2 in the
 Lease
 Company or Operator
 SE $\frac{1}{4}$ SW $\frac{1}{4}$ of Sec. 17, T. 20S, R. 30E, N. M. P. M.,
 Barber Field, Eddy County.

The dates of this work were as follows: February 12, 13, 14, 15, 1954

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on February 2, 1954
 and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED
 On Friday 2-12-54, 7" csg was perforated with 2 shots by Lane-Wells @ 1090' (at base of salt). Baker retainer was set at 1060', and hole was cemented with 120 sack of cement. On 2-13-54 temperature survey was run by B-J Co., and cement was found to have come up to 280' from 1060'. Tubing with packer was then run and hole in 7" csg found at 125'. 50 sack squeeze job was run in 7" csg on 2-14-54, using in all cases 4% Ca Cl₂ solution. Circulation was not obtained. 15 sack cement job was again run on 2-14-54. On 2-15-54 hole could be filled with water and stand full inside and outside of 7" csg. Another squeeze job was run, which circulated to the surface and filled up around 8" csg. in hole. Job was successful and completed 2-15-54.

Witnessed by _____ Name _____ Company _____ Title _____

Subscribed and sworn before me this 17th

I hereby swear or affirm that the information given above is true and correct.

day of February

1954

Name

Position

Owner

Representing

Neil H. Wills

Company or Operator

My commission expires

8-21-54

Address

Box 529, Carlsbad, New Mexico

Remarks:

Name

Title

3

1
1

1

✓

10/10/10