

N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

H.C. Wells, et al

Carlsbad, New Mexico

Company or Operator

Address

State No. 1

Well No. 1

in Lot No. 2

of Sec. 19

T. 20-S

R. 30-E, N. M. P. M., Getty Field, Eddy County.

Well is 330 feet south of the North line and 330 feet west of the East line of

If State land the oil and gas lease is No. 132230 Assignment No. none

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is Address

Drilling commenced Feb. 23rd, 1937 Drilling was completed Mar. 25th, 1937

Name of drilling contractor E.P. Moran Address Carlsbad N.M.

Elevation above sea level at top of casing feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from to No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 187 to 195 feet. small amount

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
10 1/2	40#	8		150 ft.				
8 1/4	30	8		385				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
12 1/2	10 1/2	150	none			
10	8 1/4	385	50			

PLUGS AND ADAPTERS

Heaving plug—Material None Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		None				

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet

Cable tools were used from 0 feet to 1790 feet, and from feet to feet

PRODUCTION

Put to producing, 19

The production of the first 24 hours was None barrels of fluid of which % was oil; %

emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

S.J. Poteet

Driller

Coleman Kerr

Driller

E.P. Moran

Driller

Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 14 day of May, 1937

Carlsbad, N.M.

May 11th, 1937

Name H.C. Wells

Partner

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	20	20	Caliche
20	40	20	Red Rock
40	85	45	Red Sand
85	95	10	Gravel
95	110	15	Red Sand
110	140	30	Red Sand
140	175	35	Red Sand ... Set 10" casing at 150 ft.
175	179	4	Brown Shale
179	198	19	Gravel
198	208	10	Lime
208	215	7	Anhydrite
215	225	10	Anhydrite
225	235	10	Red Rock
235	265	30	Red Rock
265	270	5	Blue Shale
270	285	15	Red Beds
285	330	45	Red Beds
330	360	30	Red Rock
360	370	10	Red Beds
370	385	15	Salt Set 8" in casing at 385 ft.
385	425	40	Salt-Hard
425	470	45	Salt-Red & Brown
470	525	55	Salt & Potash-Red
525	555	30	Salt-Brown & Red
555	725	170	Salt & Potash
725	745	20	Red Beds
745	785	40	Salt-Hard & Brown
785	820	35	Red Beds & Salt
820	855	35	Salt & Potash
855	870	15	Salt-Extra Hard
870	950	80	Salt
950	990	40	Hard Salt-Red & Brown
990	1040	50	Salt
1040	1070	30	Salt-Brown & Firm
1070	1090	20	Reddish Brown Salt
1090	1130	40	Sand & Red Beds
1130	1170	40	Salt
1170	1175	5	Anhydrite & Salt
1175	1190	15	Anhydrite & Salt
1190	1200	10	White Salt
1200	1220	20	Anhydrite
1220	1265	45	Salt
1265	1310	45	Salt & Potash
1310	1390	80	Salt & Potash
1390	1398	8	Salt
1398	1402	4	Grey Sticky Shale
1402	1465	63	Red Beds
1465	1475	10	Red Rock
1475	1553	78	Broken Formation
1553	1560	7	Anhydrite
1560	1570	10	Red Rock
1570	1590	20	Salt, Potash, & Anhydrite
1590	1606	16	Blue Shale
1606	1630	24	Anhydrite
1630	1660	30	White Salt
1660	1695	35	Salt
1695	1720	35	Anhydrite & Salt
1720	1740	20	White Anhydrite-Hard
1740	1755	15	Anhydrite
1755	1770	15	Lime
1770	1785	15	Dark Grey Lime
1785	1790	5	Sulphur Water- Hole Abandoned