

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	X
NOTICE OF INTENTION TO DEEPEN WELL			

Carlsbad, New Mexico

Place

October 13, 1938

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

DUPLICATE

Gentlemen:

Following is a notice of intention to do certain work as described below at the Neil H. Wills et al

State "A"

Well No. 2 in NE

Company or Operator

Lease

of Sec. 19, T. 20, R. 30, N. M. P. M., Barber Field,

County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

Previous to this time the well was plug back from 1650' with a wood plug and 250# lead wool to shut off bottom water. On a pump test, the well averaged about 4 barrels oil per day. The well was then shot with 20 qts. from 1485'-95' on Oct. 5, 1938 and treated by Dow on Oct. 7, 1938 with 1000 gallons acid. The results were not satisfactory and the well will be plugged to wit:

Fill hole with rock from TD to 1300' and then place 200 # lead wool in the 7" csg. followed with a 5 sax cement plug. 7" csg. will then be knocked off above the plug and the hole filled with mud from the plug to the bottom of the 8" csg. at 380'. A 5 sax cement plug will be placed in the bottom of the 8" csg. and then the 8 1/2" will be knocked off @ about 200' and salvaged. The hole will then be filled with mud to the surface and a marker erected over the location.

Approved OCT 15 1938, 19____
except as follows:


Neil H. Wills

Company or Operator

By Neil H. WillsPosition Owner

Send communications regarding well to

OIL CONSERVATION COMMISSION,

Name Neil H. WillsAddress Box 529, Carlsbad, New MexicoBy John C. WillsTitle OIL & GAS INSPECTOR

HOBBS OFFICE