NEW . XICO OIL CONSERVATION COM. SION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable on the rejection by the Commission or agent of the plan submitted. The plan as approved should be followed to the rejection by the Commission or agent of the plan submitted.

	NOTICE OF INTENTION TO SHOOT OR	
TICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO PULL OR NOTICE OF INTENTION TO PULL OR	
TICE OF INTENTION TO CHANGE PLANS	OTHERWISE ALTER CADING	
OTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL	XX
OTICE OF INTENTION TO DEEPEN WELL		
	exico March 8, 1944 Place Date	
IL CONSERVATION COMMISSION,		
anta Fe, New Mexico.		
entlemen:	k as described below at the Well No. 1 in	MW / NW / INE /
Tommon HOTTON DIM LO TIT		1117 - 1117 - 17 - 17 - 17 - 17 - 17 -
Company or Operator f Sec. 29, T. 20S, R. 30	E N. M. P. M.,	Field,
f Sec. Con	ntv.	
TO THE PART OF	OF PROPOSED PLAN OF WORK	
FULL DETAILS	RULES AND REGULATIONS OF THE COMMISSION	
FOLLOW INSTRUCTIONS IN 1222	· -· -	
	plug wells as follows:	
Fill hole with gravel bridge, dump 5 sacks crock bridge, dump 5 sa		hich cks
Fill hold with gravel bridge, dump 5 sacks crock bridge, dump 5 sawill be inside of the cment, fill hole with in cement.	plug wells as follows: from 1,802 to 1,732 set rock ement, fill hole with mud to 1,445, set cks cement, fill hole with mud to 535, w surface pipe, set rock bridge, dump 5 sa mud to surface and set regulation marker	
Fill hold with gravel bridge, dump 5 sacks crock bridge, dump 5 sawill be inside of the cment, fill hole with in cement. Approved April 17, 1944	plug wells as follows: from 1,802 to 1,732 set rock ement, fill hole with mud to 1,145, set cks cement, fill hole with mud to 535, w surface pipe, set rock bridge, dump 5 sa mud to surface and set regulation marker (Signed) A. H. Hover Company or Operator	
Fill hold with gravel bridge, dump 5 sacks crock bridge, dump 5 sawill be inside of the cment, fill hole with in cement.	plug wells as follows: from 1,802 to 1,732 set rock ement, fill hole with mud to 1,445, set cks cement, fill hole with mud to 535, w surface pipe, set rock bridge, dump 5 sa mud to surface and set regulation marker (Signed) A. H. Hover Company or Operator By	
Fill hold with gravel bridge, dump 5 sacks crock bridge, dump 5 sawill be inside of the cment, fill hole with in cement. Approved April 17, 1944	plug wells as follows: from 1,802 to 1,732 set rock ement, fill hole with mud to 1,145, set cks cement, fill hole with mud to 535, w surface pipe, set rock bridge, dump 5 sa mud to surface and set regulation marker (Signed) A. H. Hover Company or Operator	
Fill hold with gravel bridge, dump 5 sacks crock bridge, dump 5 sawill be inside of the cment, fill hole with in cement. Approved April 17, 1944	plug wells as follows: from 1,802 to 1,732 set rock ement, fill hole with mud to 1,445, set cks cement, fill hole with mud to 535, w surface pipe, set rock bridge, dump 5 sa mud to surface and set regulation marker (Signed) A. H. Hover Company or Operator By Position Send communications regarding	well to