

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPL. (Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-070286

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Dos Hermanos - Y-SR

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 33-20S-30E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

WILLIAM A. & EDWARD R. HUDSON

3. ADDRESS OF OPERATOR

Box #198, Artesia, New Mexico 88310

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

1980' from north and west lines, Sec. 33-20S-30E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On April 21, 1981 with tubing set at 1682' (open ended), pumped 125 sacks Class "C" cement with 1/4# Flo Cell/sx. Pulled 1100' tubing and shut down 3 hours. Tagged top of cement at 1314'. Raised tubing to 1290'. Pumped 165 sx. Class "C" cement. Pulled tubing. Shut-in overnite. April 22 - Tagged top of cement at 1225'. Set tubing at 1200'. Pumped 150 sx. Class "C" cement + 4% CaCl + 3/4# Flo Cell. Pulled tubing and shut down for 3 hours. Tagged cement at 1225'. Pumped 150 sx. and shut down 3 hours. Pumped 200 sx. 10# salt, 1# Flo Cell, pulled tubing. Shut-in overnite. Apr. 23 - Tagged cement at 1130'. Raised tubing to 1110'. Pumped 50 sx. Class "C" cement with 1# Flo Cell + 4% CaCl. Fluid circulated to surface. Pulled tubing. Shut down 2 hours. Tagged cement at 617'. Set tubing at 586'. Pumped 150 sx. Class "C" neat cement. Cement circulated to surface. Installed 4" pipe marker.

Location is ready for inspection.

Post ID-2
8-1-86
PVA

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Consulting Engineer

DATE May 7, 1981

(This space for Federal or State office use)

APPROVED BY

TITLE

ACTING AREA MANAGER
CARLEAD RESOURCE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

