

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSION

Drawer DD

Artesia, NM FORBIDDEN

Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Hudson & Hudson, Inc.

3. Address and Telephone No.

P.O. Box 9, Maljamar, NM 88264

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec. 33 T-20-S R-30-E SW $\frac{1}{4}$ NE $\frac{1}{4}$ 1980' FNL & 1980' FWL

Unit G

5. Lease Designation and Serial No.

NM0733

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

G

8. Well Name and No.

Gulf Fed. #1

9. API Well No.

30-015-04723

10. Field and Pool, or Exploratory Area

Dos Hermonos, Yates SR

11. County or Parish, State

Eddy, NM

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- 1) Spot 86 sacks cement, plug at 1633', W.O.C., tag cement top at 1453' plug is low,
Spot 40 sacks cement at 1453', W.O.C., tag cement top at 1319', plug is low,
Spot 18 sacks cement at 1453', W.O.C., tag cement top at 1311', plug is low,
Spot 100 sacks cement @ 1311', W.O.C., tag cement top at 710'

- 2) Load hole with mud

- 3) Spot 25 sacks cement, plug at 470'

- 4) Spot 15 sacks cement, plug at 50' to surface

- 5) Job completed 7-10-95

RECEIVED

AUG 20 1995

OIL CON. DIV.
DIST. 2

Approved as to plugging of the well bore
Liability under bond is retained until
surface restoration is completed.

CAT
ARCH

AUG 8 11 05 AM '95

RECEIVED

Post ID-2
9-15-95
PKA

I hereby certify that the foregoing is true and correct

Signed A.B. Smith

Title Prod. Supt.

Date 7/21/95

(This space for Federal or State office use)

(ORIG. SCD.) JOE G. LARA

PETROLEUM ENGINEER

Date 8/28/95

Approved by
Conditions of approval, if any: