

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LOCATE WELL CORRECTLY

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Title **Geologist**

The summary on this page is for the condition of the well at above date.

Commenced drilling July 28, 1956 Finished drilling August 13, 1956

(Denote gas by G)

No. 1, from 1628 to 1630 No. 4, from _____ to _____
 No. 2, from _____ to _____ No. 5, from _____ to _____
 No. 3, from _____ to _____ No. 6, from _____ to _____

No. 1, from 210 to 220 No. 3, from _____ to _____
No. 2, from _____ to _____ No. 4, from _____ to _____

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated		Purpose
							From—	To—	
8-5/8"	24.5		J-55	524	Outside				
7"	20		J-55	1414	Outside				
HISTORY OF OIL OR GAS WELL									

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
8-5/8"	51A	125 SK			
7"	161A	216 SK			

Heaving plug—Material ----- Length ----- Depth set -----
Adapters—Material ----- Size -----

[illegible]

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet
Cable tools were used from 9 feet to 1630 feet, and from _____ feet to _____ feet

August 22, 1956 Put to producing August 13, 1956

The production for the first 24 hours was 76 barrels of fluid of which 100 % was oil; ----- % emulsion; ----- % water; and ----- % sediment. Gravity. °Ré. 27

If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____

Rock pressure, lbs. per sq. in. _____

EMPLOYEES	
O. E. Wood	Driller
Frank Allen	Driller
J. C. Alexander	Driller
	Driller

FROM-	TO-	TOTAL FEET	FORMATION
0	10	10	Caliche
10	150	140	Red sandy shale
150	194	44	Anhydrite
194	199	5	Red Shale
199	245	46	Chat & Anhydrite - 2½ blrs. wtr. per hr. 210' - 220'
260	328	68	Anhydrite
328	330	2	Blue Shale
330	355	25	Anhydrite & Sand
355	370	15	Lime
370	385	15	Broken Anhydrite
385	425	40	Red Shale
425	460	35	Blue Shale
460	495	35	Red Shale & Anhydrite
495	510	15	Red Shale & Potash
510	549	39	Anhydrite, Potash & Salt
549	1155	605	Potash & Salt
1155	1175	20	Anhydrite
1175	1250	75	Salt & Potash
1250	1310	60	Anhydrite
1310	1475	165	Lime
1475	1505	30	Broken Lime & Shale
1505	1527	22	Lime
1527	1540	13	Broken Lime
1540	1555	15	Red Shale

