

NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELL

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON REPAIRING WELL
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	REPORT ON PULLING OR OTHERWISE ALTERING CASING
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON DEEPENING WELL
REPORT ON RESULT OF PLUGGING OF WELL X	

Carlsbad, New Mexico

August 24, 1932

Place

Date

OIL CONSERVATION COMMISSION
Santa Fe, New Mexico.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
Pioneer Oil Company State _____ Well No. 1 in the _____
Company or Operator _____ Lease _____
SW SW SE of Sect. 36, T. 20, R. 30, N. M. P. M.,
Field, Eddy County

The dates of this work were as follows: _____

Notice of intention to do the work was (was not) submitted on Form C-102 on _____ 19_____
and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

The reported depth of this well was 1250'. From information available it is very possible that 1000' was the bottom of the hole. When Mr. Caston tried to clean this well out he found bottom at 580'. At that time he rigged up a chisel bottom clean out bailer and made 12' by drilling with the clean out bailer. All of the cuttings brought out of the hole were sand and apparently the hole had sanded up from the bottom to this point, possible thru a line cut in the pipe above 580'. We set 5 sax of cement at 580' inside of the pipe and then shot the pipe off and run 10 sax of cement after we had lifted the pipe to let the cement in behind the pipe. That cement filled the hole a short ways above the shot but apparently part of it went behind the pipe.

From that point we filled the hole with mud laden fluid & removed the 10" after shooting it off at 300', then filled the hole to the top with mud laden fluid & set a peice of 8" pipe that had been made into a bailer for a marker in concrete. NOTE:

Witnessed by _____ day of _____, 19_____
Subscribed and sworn to before me this _____ day of _____, 19_____
I hereby swear or affirm that the information given above is true and correct.

This method of plugging was approved by Dr. E. H. Wells after we found that it was impossible to clean out to the bottom.

Notary Public

Representing

Company or Operator

My Commission expires _____

Address _____

Remarks:

J. D. Hunter

Name

Inspector

Title