


(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Las Cruces

Lease No. 034293

Unit



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<input checked="" type="checkbox"/>		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Midland, Texas, November 22, 1944

Genevieve Riley

Well No. 1 is located 660 ft. from N line and 1980 ft. from E line of sec. 15

SE 1 SW 1, Sec. 15  
(1/4 Sec. and Sec. No.)

20-S  
(Twp.)

31-E  
(Range)

N. M. P. M.  
(Meridian)

Wildcat  
(Field)

Eddy  
(County or Subdivision)

New Mexico  
(State or Territory)

The elevation of the derrick floor above sea level is 3458 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Total Depth, 2850' - Lime.

10-3/4" casing cemented at 344' with 350 sacks. 8-5/8" casing cemented at 870' with 50 sacks.

This well has been drilled to 2850' without encountering any oil or gas producing horizons. At 2825' to 2836' sulfur water entered the hole at the rate of 5 bailers per hour, and at the present total depth, there is more than 2000' of water standing in the hole.

We now desire permission to plug and abandon this well as follows:

(See attached sheet)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company THE TEXAS COMPANY

Address Box 1270

Midland, Texas

By

Title District Superintendent

GENEVIEVE RILEY WELL NO. 1

Set a 20-sack cement plug from total depth to approximately 2780' to shut off sulfur water. Set a 35-sack quick-set cement plug at the base of the salt, from 2375' to approximately 2275'. Spot 20 sacks of cement at the top of the salt and in the bottom of the 8-5/8" casing, from approximately 920' to 825'. Attempt to part and pull approximately 500' of 8-5/8" casing. Leave all 10-3/4" casing cemented in the hole, and set customary 4" pipe marker in the top of the hole with approximately 20 sacks of cement. The hole will be filled with heavy, viscous mud before pulling any casing or spotting the above cement plugs. All mud and cement will be pumped in through tubing.

The above confirms telephone conversation and approval by your office as of November 21, 1944.

