


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Las Cruces**

Lease No. **029179**



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....		SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	X		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Midland, Texas, November 2, 1944

F. S. Skidmore
Well No. **1** is located **660** ft. from **S** line and **660** ft. from **W** line of sec. **24**
SW 1/4 Sec. 24 **20-S** **31-E** **N. M. P. M.**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wilcoat **Eddy** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **3515** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Total Depth, 2962' - Lime.

10-3/4" casing cemented at 400' with 100 sacks. 8-5/8" casing cemented at 895' with 50 sacks.

This well has been drilled to 2962' without encountering any oil or gas producing horizons. At 2845', sulphur water entered the hole to a height of 2000'. We now desire permission to plug and abandon this well as follows:

(See attached sheet)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **THE TEXAS COMPANY**

Address **Box 1270**

Midland, Texas

By _____

Title **District Superintendent**

F. S. SKIDMORE WELL NO. 1

Set a 40-sack cement plug from total depth to approximately 2820' to shut off sulphur water. Set a 35-sack quick-set cement plug at the base of the salt, from 2330' to approximately 2230'. Spot 20 sacks of cement at the top of the salt and in the bottom of the 8-5/8" casing, from approximately 970' to 875'. Attempt to part and pull approximately 400' of 8-5/8" casing. Leave all 10-3/4" casing cemented in the hole, and set customary 4" pipe marker in the top of the hole with approximately 20 sacks of cement. The hole will be filled with heavy, viscous mud before pulling any casing or spotting the above cement plugs. All mud and cement will be pumped in through tubing.

The above confirms telephone conversation and approval by your office as of November 2, 1944.

1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 12. 13. 14. 15. 16. 17. 18. 19. 20. 21. 22. 23. 24. 25. 26. 27. 28. 29. 30. 31. 32. 33. 34. 35. 36. 37. 38. 39. 40. 41. 42. 43. 44. 45. 46. 47. 48. 49. 50. 51. 52. 53. 54. 55. 56. 57. 58. 59. 60. 61. 62. 63. 64. 65. 66. 67. 68. 69. 70. 71. 72. 73. 74. 75. 76. 77. 78. 79. 80. 81. 82. 83. 84. 85. 86. 87. 88. 89. 90. 91. 92. 93. 94. 95. 96. 97. 98. 99. 100.

Set a 40-sack cement plug from total depth to approximately 10.0' to about 10' higher water. Set a 35-sack cement plug from the base of the salt, from 2330' to approximately 2350'. Set 30 sacks of cement at the top of the salt and 10 sacks of cement at the top of the casing, from approximately 970' to 975'. Attempt to part and pull approximately 400' of 8-5/8" casing. Leave all 10-3/4" casing cemented in the hole, and set casing in the top of the hole with approximately 30 sacks of cement. The hole will be filled with heavy, viscous mud before pulling any casing or pulling the casing cement plugs. All mud and cement will be pumped in through tubing.

The above conditions require consultation and approval by your office as of 10/1/54.