

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

plug

plug

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Gates & Co.</u>		Lease <u>Leaf State A</u>		Well # <u>1</u>	
Location of Well	Unit <u>D</u>	Section <u>2</u>	Township <u>20</u>	Range <u>27</u>	County <u>Eddy</u>
Drilling Contractor	<u>Co. Seels</u>		Type of Equipment <u>Rotary</u>		
<u>APPROVED CASING PROGRAM</u> ^{IN HOLE}					
2400' G Set					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>11</u>	<u>8 7/8</u>	<u>24</u>	<u>New</u>	<u>267 1/2</u>	<u>50 75</u>
<u>7 7/8</u>	<u>4 1/2 to 5 1/2</u>	<u>9.5 to 14</u>	<u>New</u>	<u>DP</u>	<u>Circulate</u>
Casing Data:					
Surface <u> </u> joints of <u> </u> inch <u> </u> # Grade <u> </u>					
<u> </u> (Approved) (Rejected) <u> </u>					
Inspected by <u> </u> date <u> </u>					
Cementing Program					
Size of hole <u> </u> Size of Casing <u> </u> Sacks cement required <u> </u>					
Type of Shoe used <u> </u> Float collar used <u> </u> Btm 3 jts welded <u> </u>					
TD of hole <u>2420</u> Set <u> </u> Feet of <u> </u> Inch <u> </u> # Grade <u> </u>					
New-used csg. @ <u> </u> with <u> </u> sacks neat cement around shoe					
+ <u> </u> sack <u> </u> additives <u> </u>					
Plug down @ <u> </u> (AM) (PM) Date <u> </u>					
Cement circulated <u> </u> No. of Sacks <u> </u>					
Cemented by <u>DENTON</u> Witnessed by <u>LOBLEY</u> 8-19-61					
Temp. Survey ran @ <u> </u> (AM) (PM) Date <u> </u> top cement @ <u> </u>					
Casing test @ <u> </u> (AM) (PM) Date <u> </u>					
Method Used <u> </u> Witnessed by <u> </u>					
Checked for shut off @ <u> </u> (AM) (PM) Date <u> </u>					
Method used <u> </u> Witnessed by <u> </u>					
Remarks: <u>On 8-6-61 set 8 7/8 @ 267 1/2 (not inspected) & out @ 280 1/2</u>					
<u>Hole lost to cement before getting plug.</u>					

1. 24 240 2420 T.D.
2. 10 240 1600
3. 10 240 1300
4. 10 240 600
5. 10 240 267 1/2
6. 4 240 1000