FORD 9-SGIA	Budget Bureau 42-R358.2. Approval expires 12-31-52.
	U. M. O. C. COUM (SUBMIT IN TRIPLICATE) Lease No. 085201 N.M.
	UNITED STATES DEPARTMENT OF THE INTERIOR
6	GEOLOGICAL SURVEY
SUNDRY N	COTICES AND REPORTS ON WELLS
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	Subsequent report of shooting or acidizing
NOTICE OF INTENTION TO TEST WATER S	SHUT-OFF SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR I	· · · · · · · · · · · · · · · · · · ·
NOTICE OF INTENTION TO SHOOT OR ACI	
NOTICE OF INTENTION TO PULL OR ALTE	
NOTICE OF INTENTION TO ABANDON WEL	
(INDICATE A	ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	DECEMBER 17 , 19 63
Well No1 is located	<u>660</u> ft. from ${ I \atop S}$ line and <u>1980</u> ft. from ${ I \atop W}$ line of sec. <u>9</u>
SW/4 SECTION 9	T-21-S R-25-E NMPM (Twp.) (Range) (Meridian)
WILDCAT (Field)	EDDY NEW MEXICO (County or Subdivision) (State or Territory)
GROUND L	
	DETAILS OF WORK
(State names of and expected depths to obj	jective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- ing points, and all other important proposed work)
11/23/63 - Ran 13 jts. (Cemented with 250 sacks flocel followed with 100 cement 338'. Ran 1" pip with 300 sacks in 3 stag	jective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coment-
11/23/63 - Ran 13 jts. (Cemented with 250 sacks flocel followed with 100 cement 338'. Ran 1" pip with 300 sacks in 3 stag pea gravel. Finished ce	jective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coment- ing points, and all other important proposed work) (389') of 13-3/8", 48#, H-40 Casing and set at 406'. of Incor with 2% calcium chloride and 4% gel and 1/4#) sacks Incor Neat. Plug down at 1:45 p.m. Top of be to 330' on outside of 13-3/8" casing and comented ges. Top of cement 28' from surface and filled with
11/23/63 - Ran 13 jts. (Cemented with 250 sacks flocel followed with 100 cement 338'. Ran 1" pip with 300 sacks in 3 stag pea gravel. Finished ce	jective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coment- ing points, and all other important proposed work) (389') of 13-3/8", 48#, H-40 Casing and set at 406'. of Incor with 2% calcium chloride and 4% gel and 1/4#) sacks Incor Neat. Plug down at 1:45 p.m. Top of be to 330' on outside of 13-3/8" casing and comented ges. Top of cement 28' from surface and filled with
11/23/63 - Ran 13 jts. (Cemented with 250 sacks flocel followed with 100 cement 338'. Ran 1" pip with 300 sacks in 3 stag pea gravel. Finished ce	jective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coment- ing points, and all other important proposed work) (389') of 13-3/8", 48#, H-40 Casing and set at 406'. of Incor with 2% calcium chloride and 4% gel and 1/4#) sacks Incor Neat. Plug down at 1:45 p.m. Top of be to 330' on outside of 13-3/8" casing and comented ges. Top of cement 28' from surface and filled with
11/23/63 - Ran 13 jts. (Cemented with 250 sacks flocel followed with 100 cement 338'. Ran 1" pip with 300 sacks in 3 stag pea gravel. Finished ce	jective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coment- ing points, and all other important proposed work) (389') of 13-3/8", 48#, H-40 Casing and set at 406'. of Incor with 2% calcium chloride and 4% gel and 1/4#) sacks Incor Neat. Plug down at 1:45 p.m. Top of be to 330' on outside of 13-3/8" casing and comented ges. Top of cement 28' from surface and filled with
11/23/63 - Ran 13 jts. (Cemented with 250 sacks flocel followed with 100 cement 338'. Ran 1" pip with 300 sacks in 3 stag pea gravel. Finished ce drilling out cement.	jective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- ing points, and all other important proposed work) (389') of 13-3/8", 48#, H-40 Casing and set at 406'. of Incor with 2% calcium chloride and 4% gel and 1/4# 0 sacks Incor Neat. Plug down at 1:45 p.m. Top of be to 330' on outside of 13-3/8" casing and cemented ges. Top of cement 28' from surface and filled with ementing at 5:00 a.m. on 11/24/63. WOC 24 hours before
11/23/63 - Ran 13 jts. (Cemented with 250 sacks flocel followed with 100 cement 338'. Ran 1" pip with 300 sacks in 3 stag pea gravel. Finished ce drilling out cement.	<pre>jective sands; show sizes, weights,'and lengths of proposed casings; indicate mudding jobs, cement- ing points, and all other important proposed work) (389') of 13-3/8", 48#, H-40 Casing and set at 406'. of Incor with 2% calcium chloride and 4% gel and 1/4# 0 sacks Incor Neat. Plug down at 1:45 p.m. Top of be to 330' on outside of 13-3/8" casing and cemented ges. Top of cement 28' from surface and filled with ementing at 5:00 a.m. on 11/24/63. WOC 24 hours before were approved in writing by the Geological Survey before operations may be commenced.</pre>
11/23/63 - Ran 13 jts. (Cemented with 250 sacks flocel followed with 100 cement 338'. Ran 1" pip with 300 sacks in 3 stag pea gravel. Finished ce drilling out cement.	jective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- ing points, and all other important proposed work) (389') of 13-3/8", 48#, H-40 Casing and set at 406'. of Incor with 2% calcium chloride and 4% gel and 1/4# 0 sacks Incor Neat. Plug down at 1:45 p.m. Top of be to 330' on outside of 13-3/8" casing and cemented ges. Top of cement 28' from surface and filled with ementing at 5:00 a.m. on 11/24/63. WOC 24 hours before
11/23/63 - Ran 13 jts. (Cemented with 250 sacks flocel followed with 100 cement 338'. Ran 1" pip with 300 sacks in 3 stag pea gravel. Finished ce drilling out cement. I understand that this plan of work mu Company	<pre>jective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- ing points; and all other important proposed work) (389') of 13-3/8", 48#, H-40 Casing and set at 406'. of Incor with 2% calcium chloride and 4% gel and 1/4# 0 sacks Incor Neat. Plug down at 1:45 p.m. Top of be to 330' on outside of 13-3/8" casing and cemented ges. Top of cement 28' from surface and filled with ementing at 5:00 a.m. on 11/24/63. WOC 24 hours before ust receive approval in writing by the Geological Survey before operations may be commenced. PHY H. BAXTER DING</pre>
11/23/63 - Ran 13 jts. (Cemented with 250 sacks flocel followed with 100 cement 338'. Ran 1" pip with 300 sacks in 3 stag pea gravel. Finished ce drilling out cement. I understand that this plan of work mu Company	<pre>jective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- ing points; and all other important proposed work) (389') of 13-3/8", 48#, H-40 Casing and set at 406'. of Incor with 2% calcium chloride and 4% gel and 1/4# 0 sacks Incor Neat. Plug down at 1:45 p.m. Top of be to 330' on outside of 13-3/8" casing and cemented ges. Top of cement 28' from surface and filled with ementing at 5:00 a.m. on 11/24/63. WOC 24 hours before ust receive approval in writing by the Geological Survey before operations may be commenced. PHY H. BAXTER DING</pre>
11/23/63 - Ran 13 jts. (Cemented with 250 sacks flocel followed with 100 cement 338'. Ran 1" pip with 300 sacks in 3 stag pea gravel. Finished ce drilling out cement. I understand that this plan of work mu Company	<pre>jective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- ing points; and all other important proposed work) (389') of 13-3/8", 48#, H-40 Casing and set at 406'. of Incor with 2% calcium chloride and 4% gel and 1/4# 0 sacks Incor Neat. Plug down at 1:45 p.m. Top of be to 330' on outside of 13-3/8" casing and cemented ges. Top of cement 28' from surface and filled with ementing at 5:00 a.m. on 11/24/63. WOC 24 hours before ust receive approval in writing by the Geological Survey before operations may be commenced. PHY H. BAXTER DING</pre>
11/23/63 - Ran 13 jts. (Cemented with 250 sacks flocel followed with 100 cement 338'. Ran 1" pip with 300 sacks in 3 stag pea gravel. Finished ce drilling out cement. I understand that this plan of work mu Company	<pre>jective sands; show sizes, weights/and lengths of proposed casings; indicate mudding jobs, coment- ing points, and all other important proposed work) (389') of 13-3/8", 48#, H-40 Casing and set at 406'. of Incor with 2% calcium chloride and 4% gel and 1/4# 0 sacks Incor Neat. Plug down at 1:45 p.m. Top of be to 330' on outside of 13-3/8" casing and cemented ges. Top of cement 28' from surface and filled with ementing at 5:00 a.m. on 11/24/63. WOC 24 hours before wurt receive approval in writing by the Geological Survey before operations may be commenced. PHY H. BAXTER 2704 By M. January By M.</pre>