

(SUBMIT IN TRIPLICATE)

CT ENGINEER DEPARTMENT OF THE INTERIOR

Budget Bure Form Approv	au No/42-R358.4.
Land Office	063494
Unit	"7"

SUNDRY NOTICES AND REPORTS ON WELLS

	II II		
NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	3
NOTICE OF INTENTION TO TEST WATER SI		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR R		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACII		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER		SUPPLEMENTARY WELL HISTORY	·-·
NOTICE OF INTENTION TO ABANDON WELL			
(INDICATE AB	BOVE BY CHECK MARK NATU	RE OF REPORT, NOTICE, OR OTHER DATA)	
		Hay 24	1963
Virginia Lee	ssa (N) (F)	
Well Nois located _	ft. from [N	line and ft. from line	of sec. 10
NE ME SEC. 10	20s 27£	MMFM	\circ
Wildeat	(Twp.) (Range	(Meridian)	o (4)
(Field)	(County or Subdi	vision) (State or Territory	C. 62.6
itate names of and expected depths to objec	DETAILS (hts, and lengths of proposed casings: indicate mu	dding the princip
lugged and abandoned	tive sands; show sizes, weiging points, and all other in well on may the heavy saud to 1372 feet.	this, and lengths of proposed casings; indicate musportant proposed work) 18, 1963, as follows: 10 550 feet. Spotted conspicted conspicted coment plug fi	ont.
Filled hole with plug from 1472 feet to 50 feet to 450 feet.	tive and a slow sizes, weighting points, and all other in a well on may the heavy saud to 1372 feec. Fulled 405	this, and lengths of proposed easings; indicate mulportant proposed work) 18, 1963, as follows: to 550 feet. Spotted conspetted consent plug fraction of 8 5/8" casing. regulation marker in 25	ment ros
Filled hole with the state of t	tive and a slow sizes, weighting points, and all other in a well on may the heavy saud to 1372 feec. Fulled 405	this, and lengths of proposed easings; indicate musportant proposed work) 18, 1963, as follows: 10 550 feet. Spotted compated compated compated compated files.	Seent ros
Filled hole with plug from 1472 feet to 550 feet to 450 feet.	tive and a slow sizes, weighting points, and all other in a well on may the heavy saud to 1372 feec. Fulled 405	this, and lengths of proposed easings; indicate mulportant proposed work) 18, 1963, as follows: to 550 feet. Spotted conspetted consent plug fraction of 8 5/8" casing. regulation marker in 25	Seent ros
Filled hole with plug from 1472 feet to 550 feet to 450 feet. Filled hole with heavy plug at surface.	tive ands; show sizes, weiging points, and all other in well on May the heavy saud to 1372 feet. Fulled 405 ry madend set	this, and lengths of proposed easings; indicate multiportant proposed work) 18, 1963, as follows: to 350 feet. Spotted constant plug from the feet of 8 5/8" casing. REGEIVE MAR 1 2 1964 by the Geological Survey held of Spotted marks.	seent rom
Filled hole with plug from 1472 feet to 550 feet to 450 feet. Filled hole with heavy plug at Surface.	tive sands; show sizes, weiging points, and all other in a well on may the heavy said to 1372 feet. Fulled 405 Ty madend set	this, and lengths of proposed easings; indicate musportant proposed work) 18, 1963, as follows: to 350 feet. Spotted constant plug from the spotted coment plug from the spotted of 85/5" casing. RECEIVE MAR 1 2 1964	seent rom
Filled hole with plug from 1472 feet to 550 feet to 450 feet. Filled hole with heavy plug at surface.	tive sands; show sizes, weiging points, and all other in a well on may the heavy saud to 1372 feet. Fulled 405 y madend set	this, and lengths of proposed casings; indicate musportant proposed work) 18, 1963, as follows: 18	Seent rom Seent D
Filled hole with plug from 1472 feet to 550 feet to 450 feet. Filled hole with heavy plug at surface. Tunderstand that this plan of work must company John A. Yaz	ctive sands; show sizes, weiging points, and all other in a well on May the heavy saud to 1372 feet. Fulled 405 Ty madend set	this, and lengths of proposed easings; indicate multiportant proposed work) 18, 1963, as follows: to 350 feet. Spotted constant plug from the feet of 8 5/8" casing. REGEIVE MAR 1 2 1964 by the Geological Survey held of Spotted marks.	Seent rom Seet D