				· C
		NM ULL CONS.	C .ISSION	FORM APPROVED
orm 3160-5	UNITED ST	'ATES Drawer DD		Budget Bureau No. 1004-0135 Expires: March 31, 1993
June 1990)	DEPARTMENT OF 7	THE INTERIOR rtesia, NM	8821Q	5. Lease Designation and Serial No.
	BUREAU OF LAND	MANAGEMENT		
				NM-56350 6. If Indian, Allottee or Tribe Name
	SUNDRY NOTICES AND F rm for proposals to drill or to	deepen of reently to a units	ent reservoir.	6. If Indian, Anotee of The Folio
U	se "APPLICATION FOR PERM	AII - 101 such proposale		7. If Unit or CA, Agreement Designation
1	SUBMIT IN TF	RIPLICATE	1993	n an
1. Type of Well	the second s		*	8. Well Name and No.
Oil Well XX Well	Other	a a second a	the contraction of the contracti	Lowe Staple AMR Federal
	EUM CORPORATION	(505) 748-1471	.)	9. API Well No.
3. Address and Telephone N	ch St., Artesia, NM 88	210		10. Field and Pool, or Exploratory Area
105 South 40	e, Sec., T., R., M., or Survey Description)		Wildcat Morrow 11. County or Parish, State
	& 2310' FWL of Section	22-T21S-R24E		
				Eddy Co., NM
			OTICE REPO	RT, OR OTHER DATA
		INDICATE NATURE OF N	YPE OF ACTION	
TYPE OF	SUBMISSION			Change of Plans
Notice	of Intent	Abandonment		New Construction
				Non-Routine Fracturing
XX Subseq	uent Report	Plugging Back		Water Shut-Off Million
7121		Casing Repair		Conversion to Injection
Final /	bandonment Notice	Altering Casing Other Commence	re-entry	Dispose Water
		A Other	10 000-0	(Note: Report results of multiple completion on Wel Completion or Recompletion Report and Log form.
			in and date of start	ing any proposed work. If well is directionally drill
give subsultace to	cations and more and	1	try hole mar	ker. Welded on 9-5/8"
	g out cellar, cleaned	location and removed of	lry hole mar	ker. Welded on 9-5/8"
6-9-93: Du	g out cellar, cleaned ub with 11" X 3000 sta	location and removed outing head. Set anchor	ry hole mar	ker. Welded on 9-5/8" d up BOP. Tested and tubing to 3155'.
6-9-93: Du	g out cellar, cleaned ub with 11" X 3000 sta	location and removed outing head. Set anchor	ry hole mar	ker. Welded on 9-5/8" d up BOP. Tested and tubing to 3155'.
give subsurace to 6-9-93: Du st bl	g out cellar, cleaned ub with 11" X 3000 sta ind rams to 500 psi, C sted pipe rams to 500	location and removed o arting head. Set ancho DK. TIH w/8-3/4" bit, psi, OK. NOTE: Noti	ry hole mar	ker. Welded on 9-5/8" d up BOP. Tested and tubing to 3155'.
give subsurace to 6-9-93: Du st b1 Te BL	g out cellar, cleaned ub with 11" X 3000 sta ind rams to 500 psi, C sted pipe rams to 500 M in Carlsbad about sp	location and removed o orting head. Set ancho OK. TIH w/8-3/4" bit, psi, OK. NOTE: Noti oud.	lry hole mar ors. Nipple drill colla Eied Shannor	ker. Welded on 9-5/8" ed up BOP. Tested ars and tubing to 3155'. h Shaw w/BLM with the
give subsurface to 6-9-93: Du st bl Te BL	g out cellar, cleaned ub with 11" X 3000 sta ind rams to 500 psi, C sted pipe rams to 500 M in Carlsbad about sp	location and removed outing head. Set ancho NK. TIH w/8-3/4" bit, psi, OK. NOTE: Noti bud.	Iry hole mar ors. Nipple drill colla Fied Shannor	ker. Welded on 9-5/8" ed up BOP. Tested ars and tubing to 3155'. Shaw w/BLM with the
give subsurace to 6-9-93: Du st b1 Te BL	g out cellar, cleaned ub with 11" X 3000 sta ind rams to 500 psi, C sted pipe rams to 500 M in Carlsbad about sp shed down to 4650'.	location and removed of arting head. Set ancho NK. TIH w/8-3/4" bit, psi, OK. NOTE: Noti bud. Fagged cement plug at	ry hole mar brs. Nipple drill colla fied Shannor 4650'. Dri	ing any proposed work. If well is diffectionally drill ker. Welded on 9-5/8" ad up BOP. Tested ars and tubing to 3155'. h Shaw w/BLM with the lled cement from t 5972'. Drilled
give subsurface to 6-9-93: Du st bl Te BL Wa 46	g out cellar, cleaned ub with 11" X 3000 sta ind rams to 500 psi, C sted pipe rams to 500 M in Carlsbad about sp shed down to 4650'.	location and removed of arting head. Set ancho NK. TIH w/8-3/4" bit, psi, OK. NOTE: Noti bud. Fagged cement plug at h to 5972'. Tagged ce	try hole mar brs. Nipple drill colla fied Shannor 4650'. Dri ment plug at	ker. Welded on 9-5/8" ker. Welded on 9-5/8" ad up BOP. Tested ars and tubing to 3155'. Shaw w/BLM with the lled cement from t 5972'. Drilled cement plug from
give subsurace to 6-9-93: Du st bl Te BL Wa 46	g out cellar, cleaned ub with 11" X 3000 sta ind rams to 500 psi, C sted pipe rams to 500 M in Carlsbad about sp shed down to 4650'.	location and removed of arting head. Set ancho NK. TIH w/8-3/4" bit, psi, OK. NOTE: Noti bud. Fagged cement plug at h to 5972'. Tagged ce	try hole mar brs. Nipple drill colla fied Shannor 4650'. Dri ment plug at	ker. Welded on 9-5/8" ker. Welded on 9-5/8" ad up BOP. Tested ars and tubing to 3155'. Shaw w/BLM with the lled cement from t 5972'. Drilled cement plug from
give subsurace to 6-9-93: Du st bl Te BL Wa 46 ce	g out cellar, cleaned ub with 11" X 3000 sta ind rams to 500 psi, C sted pipe rams to 500 M in Carlsbad about sp shed down to 4650'. 50-4880'. Washed down ement from 5972-6072'.	location and removed o arting head. Set ancho NK. TIH w/8-3/4" bit, psi, OK. NOTE: Noti bud. Tagged cement plug at h to 5972'. Tagged ce Washed down to 8300' n to 9366'. Drilled c	try hole mar brs. Nipple drill colla fied Shannor 4650'. Dri ment plug at	ing any proposed work. If well is diffectionally drill ker. Welded on 9-5/8" ad up BOP. Tested ars and tubing to 3155'. h Shaw w/BLM with the lled cement from t 5972'. Drilled
give subsurface to 6-9-93: Du st bl Te BL Wa 46 ce	g out cellar, cleaned ub with 11" X 3000 sta ind rams to 500 psi, C sted pipe rams to 500 M in Carlsbad about sp shed down to 4650'.	location and removed of arting head. Set ancho DK. TIH w/8-3/4" bit, psi, OK. NOTE: Noti bud. Fagged cement plug at n to 5972'. Tagged ce Washed down to 8300' n to 9366'. Drilled c ted clean.	ry hole mar ors. Nipple drill colla fied Shannor 4650'. Dri ment plug at . Drilled ement plug	ker. Welded on 9-5/8" ed up BOP. Tested ars and tubing to 3155'. h Shaw w/BLM with the lled cement from t 5972'. Drilled cement plug from from 9366-9466'. Washed
give subsurface to 6-9-93: Du st bl Te BL Wa 46 ce 83 dc	g out cellar, cleaned ub with 11" X 3000 sta ind rams to 500 psi, C sted pipe rams to 500 M in Carlsbad about sp shed down to 4650'. T 50-4880'. Washed down ement from 5972-6072'. 300-8415'. Washed down own to 9902'. Circula	location and removed of arting head. Set ancho NK. TIH w/8-3/4" bit, psi, OK. NOTE: Noti- bud. Tagged cement plug at h to 5972'. Tagged ce Washed down to 8300' n to 9366'. Drilled c ted clean.	Ary hole mar ors. Nipple drill colla fied Shannor 4650'. Dri ment plug at . Drilled ement plug	ker. Welded on 9-5/8" ed up BOP. Tested ars and tubing to 3155'. h Shaw w/BLM with the lled cement from t 5972'. Drilled cement plug from from 9366-9466'. Washed bit, drill collars and
give subsurface to 6-9-93: Du st bl Te BL Wa 46 ce 83 dc	g out cellar, cleaned ub with 11" X 3000 sta ind rams to 500 psi, C sted pipe rams to 500 M in Carlsbad about sp shed down to 4650'. T 50-4880'. Washed down ement from 5972-6072'. 300-8415'. Washed down own to 9902'. Circula	location and removed of arting head. Set ancho NK. TIH w/8-3/4" bit, psi, OK. NOTE: Noti- bud. Tagged cement plug at h to 5972'. Tagged ce Washed down to 8300' n to 9366'. Drilled c ted clean.	ry hole mar brs. Nipple drill colla fied Shannor 4650'. Dri ment plug av . Drilled ement plug gs. TIH w/	ker. Welded on 9-5/8" ker. Welded on 9-5/8" ad up BOP. Tested ars and tubing to 3155'. Shaw w/BLM with the lled cement from t 5972'. Drilled cement plug from from 9366-9466'. Washed bit, drill collars and irculated 2-1/2 hours.
give subsurface to 6-9-93: Du st b1 Te BL Wa 46 ce 83 dc TC	g out cellar, cleaned ub with 11" X 3000 sta ind rams to 500 psi, C sted pipe rams to 500 M in Carlsbad about sp shed down to 4650'. 50-4880'. Washed down ement from 5972-6072'. 800-8415'. Washed down own to 9902'. Circula OOH w/tubing, drill co ubing to 3155'. Rigge	location and removed of arting head. Set ancho DK. TIH w/8-3/4" bit, psi, OK. NOTE: Noti- bud. Fagged cement plug at h to 5972'. Tagged ce Washed down to 8300' n to 9366'. Drilled c ted clean. llars and bit. Ran lo d up on 6 line. TIH t	ry hole mar brs. Nipple drill colla fied Shannor 4650'. Dri ment plug av . Drilled ement plug gs. TIH w/	ker. Welded on 9-5/8" ker. Welded on 9-5/8" ad up BOP. Tested ars and tubing to 3155'. Shaw w/BLM with the lled cement from t 5972'. Drilled cement plug from from 9366-9466'. Washed bit, drill collars and irculated 2-1/2 hours.
give substitute to 6-9-93: Du st bl Te BL Wa 46 ce 83 dc TC tr TC	g out cellar, cleaned ub with 11" X 3000 sta ind rams to 500 psi, C sted pipe rams to 500 M in Carlsbad about sp shed down to 4650'. T 50-4880'. Washed down ement from 5972-6072'. 300-8415'. Washed down own to 9902'. Circula OOH w/tubing, drill co ubing to 3155'. Rigge OOH w/tubing, drill co	location and removed of arting head. Set ancho DK. TIH w/8-3/4" bit, psi, OK. NOTE: Noti- bud. Fagged cement plug at h to 5972'. Tagged ce Washed down to 8300' n to 9366'. Drilled c ted clean. llars and bit. Ran lo d up on 6 line. TIH t	ry hole mar brs. Nipple drill colla fied Shannor 4650'. Dri ment plug av . Drilled ement plug gs. TIH w/	ker. Welded on 9-5/8" ed up BOP. Tested ars and tubing to 3155'. h Shaw w/BLM with the lled cement from t 5972'. Drilled cement plug from from 9366-9466'. Washed bit, drill collars and
give substitute to 6-9-93: Du st bl Te BL Wa 46 ce 83 dc TC tr TC	g out cellar, cleaned ub with 11" X 3000 sta ind rams to 500 psi, C sted pipe rams to 500 M in Carlsbad about sp shed down to 4650'. 50-4880'. Washed down ement from 5972-6072'. 800-8415'. Washed down own to 9902'. Circula OOH w/tubing, drill co ubing to 3155'. Rigge	location and removed of arting head. Set ancho DK. TIH w/8-3/4" bit, psi, OK. NOTE: Noti- bud. Fagged cement plug at h to 5972'. Tagged ce Washed down to 8300' n to 9366'. Drilled c ted clean. llars and bit. Ran lo d up on 6 line. TIH t	ry hole mar brs. Nipple drill colla fied Shannor 4650'. Dri ment plug av . Drilled ement plug gs. TIH w/	ker. Welded on 9-5/8" ker. Welded on 9-5/8" ad up BOP. Tested ars and tubing to 3155'. Shaw w/BLM with the lled cement from t 5972'. Drilled cement plug from from 9366-9466'. Washed bit, drill collars and irculated 2-1/2 hours.
give substitute to 6-9-93: Du st bl Te BL Wa 46 ce 83 dc TC tr TC	g out cellar, cleaned ub with 11" X 3000 sta ind rams to 500 psi, C sted pipe rams to 500 M in Carlsbad about sp shed down to 4650'. T 50-4880'. Washed down ement from 5972-6072'. 300-8415'. Washed down own to 9902'. Circula OOH w/tubing, drill co ubing to 3155'. Rigge OOH w/tubing, drill co	location and removed of arting head. Set ancho DK. TIH w/8-3/4" bit, psi, OK. NOTE: Noti- bud. Fagged cement plug at h to 5972'. Tagged ce Washed down to 8300' n to 9366'. Drilled c ted clean. llars and bit. Ran lo d up on 6 line. TIH t	ry hole mar brs. Nipple drill colla fied Shannor 4650'. Dri ment plug av . Drilled ement plug gs. TIH w/	ker. Welded on 9-5/8" ker. Welded on 9-5/8" ad up BOP. Tested ars and tubing to 3155'. Shaw w/BLM with the lled cement from t 5972'. Drilled cement plug from from 9366-9466'. Washed bit, drill collars and irculated 2-1/2 hours.
give substitute to 6-9-93: Du st b1 Te BL Wa 46 ce 83 dc TC tu TC 7 ¹	g out cellar, cleaned ub with 11" X 3000 sta ind rams to 500 psi, C sted pipe rams to 500 M in Carlsbad about sp shed down to 4650'. T 50-4880'. Washed down ement from 5972-6072'. 300-8415'. Washed down own to 9902'. Circula DOH w/tubing, drill co ubing to 3155'. Rigge DOH w/tubing, drill co " casing rams.	location and removed of arting head. Set ancho OK. TIH w/8-3/4" bit, psi, OK. NOTE: Notico oud. Fagged cement plug at h to 5972'. Tagged ce Washed down to 8300' n to 9366'. Drilled c ted clean. llars and bit. Ran lo d up on 6 line. TIH t llars and bit. Change	ry hole mar brs. Nipple drill colla fied Shannor 4650'. Dri ment plug at . Drilled ement plug gs. TIH w/ o 9902'. C d 2-7/8" tu	ing any proposed work. If well is diffectionally drill eker. Welded on 9-5/8" ed up BOP. Tested ars and tubing to 3155'. In Shaw w/BLM with the lied cement from t 5972'. Drilled cement plug from from 9366-9466'. Washed bit, drill collars and irculated 2-1/2 hours. bing rams. Installed
give substitute to 6-9-93: Du st b1 Te BL Wa 46 ce 83 dc TC tu TC 7 ¹	g out cellar, cleaned ub with 11" X 3000 sta ind rams to 500 psi, C sted pipe rams to 500 M in Carlsbad about sp shed down to 4650'. T 50-4880'. Washed down ement from 5972-6072'. 300-8415'. Washed down own to 9902'. Circula OOH w/tubing, drill co ubing to 3155'. Rigge OOH w/tubing, drill co	location and removed of arting head. Set ancho OK. TIH w/8-3/4" bit, psi, OK. NOTE: Notico oud. Fagged cement plug at h to 5972'. Tagged ce Washed down to 8300' n to 9366'. Drilled c ted clean. llars and bit. Ran lo d up on 6 line. TIH t llars and bit. Change	ry hole mar brs. Nipple drill colla fied Shannor 4650'. Dri ment plug at . Drilled ement plug gs. TIH w/ o 9902'. C d 2-7/8" tu	ker. Welded on 9-5/8" ker. Welded on 9-5/8" ad up BOP. Tested ars and tubing to 3155'. Shaw w/BLM with the lled cement from t 5972'. Drilled cement plug from from 9366-9466'. Washed bit, drill collars and irculated 2-1/2 hours.
give substitute to 6-9-93: Du st b1 Te BL Wa 46 Ce 83 dc TC tu TC 7 ¹ 14. 1 hereby certify that SignedU	g out cellar, cleaned ub with 11" X 3000 sta ind rams to 500 psi, C sted pipe rams to 500 M in Carlsbad about sp shed down to 4650'. T 50-4880'. Washed down ement from 5972-6072'. 300-8415'. Washed down own to 9902'. Circula 00H w/tubing, drill co ubing to 3155'. Rigge 00H w/tubing, drill co " casing rams.	location and removed of arting head. Set ancho DK. TIH w/8-3/4" bit, psi, OK. NOTE: Noti- bud. Fagged cement plug at h to 5972'. Tagged ce Washed down to 8300' n to 9366'. Drilled c ted clean. llars and bit. Ran lo d up on 6 line. TIH t	ry hole mar brs. Nipple drill colla fied Shannor 4650'. Dri ment plug at . Drilled ement plug gs. TIH w/ o 9902'. C d 2-7/8" tu	ing any proposed work. If well is diffectionally drill eker. Welded on 9-5/8" ed up BOP. Tested ars and tubing to 3155'. In Shaw w/BLM with the lied cement from t 5972'. Drilled cement plug from from 9366-9466'. Washed bit, drill collars and irculated 2-1/2 hours. bing rams. Installed
give substitute to 6-9-93: Du st b1 Te BL Wa 46 Ce 83 dc TC tu TC 7 ¹ 14. I hereby certify that Signed <u>U</u>	g out cellar, cleaned ub with 11" X 3000 sta ind rams to 500 psi, C sted pipe rams to 500 M in Carlsbad about sp shed down to 4650'. T 50-4880'. Washed down ement from 5972-6072'. 300-8415'. Washed down own to 9902'. Circula DOH w/tubing, drill co ubing to 3155'. Rigge DOH w/tubing, drill co " casing rams.	location and removed of arting head. Set ancho OK. TIH w/8-3/4" bit, psi, OK. NOTE: Notico oud. Fagged cement plug at h to 5972'. Tagged ce Washed down to 8300' n to 9366'. Drilled c ted clean. llars and bit. Ran lo d up on 6 line. TIH t llars and bit. Change	ry hole mar brs. Nipple drill colla fied Shannor 4650'. Dri ment plug at . Drilled ement plug gs. TIH w/ o 9902'. C d 2-7/8" tu	hing any proposed work. If well is diffectionally drill eker. Welded on 9-5/8" ed up BOP. Tested ars and tubing to 3155'. In Shaw w/BLM with the lied cement from t 5972'. Drilled cement plug from from 9366-9466'. Washed bit, drill collars and irculated 2-1/2 hours. bing rams. Installed Date June 25, 1993
give substitute to 6-9-93: Duy st b1 Te BL Wa 46 ce 83 dc TC tu TC 14. I hereby certify that Signed (This space for Fed Approved by	g out cellar, cleaned ub with 11" X 3000 sta ind rams to 500 psi, C sted pipe rams to 500 M in Carlsbad about sp shed down to 4650'. T 50-4880'. Washed down ement from 5972-6072'. 300-8415'. Washed down own to 9902'. Circula OOH w/tubing, drill co ubing to 3155'. Rigge OOH w/tubing, drill co " casing rams.	location and removed orting head. Set ancho OK. TIH w/8-3/4" bit, psi, OK. NOTE: Notion oud. Tagged cement plug at n to 5972'. Tagged ce Washed down to 8300' n to 9366'. Drilled c ted clean. 11ars and bit. Ran 1c d up on 6 line. TIH t 11ars and bit. Change	ry hole mar brs. Nipple drill colla fied Shannor 4650'. Dri ment plug at . Drilled ement plug gs. TIH w/ o 9902'. C d 2-7/8" tu	ing any proposed work. If well is diffectionally drill ker. Welded on 9-5/8" ed up BOP. Tested ars and tubing to 3155'. h Shaw w/BLM with the lled cement from t 5972'. Drilled cement plug from from 9366-9466'. Washed bit, drill collars and irculated 2-1/2 hours. bing rams. Installed Date June 25, 1993
give substitute to 6-9-93: Duy st b1 Te BL Wa 46 Ce 83 dc TC tu TC 14. I hereby certify that Signed (This space for Fed Approved by Conditions of approx	g out cellar, cleaned ub with 11" X 3000 sta ind rams to 500 psi, C sted pipe rams to 500 M in Carlsbad about sp shed down to 4650'. T 50-4880'. Washed down ement from 5972-6072'. 800-8415'. Washed down own to 9902'. Circula 00H w/tubing, drill co ubing to 3155'. Rigge 00H w/tubing, drill co " casing rams. The foregoing is true and correct the foregoing is true and correct wal, if any:	location and removed of arting head. Set ancho DK. TIH w/8-3/4" bit, psi, OK. NOTE: Noti- bud. Tagged cement plug at a to 5972'. Tagged ce Washed down to 8300' a to 9366'. Drilled c ted clean. 11ars and bit. Ran loc d up on 6 line. TIH t 11ars and bit. Change 	ry hole mar brs. Nipple drill colla fied Shannor 4650'. Dri ment plug an . Drilled ement plug gs. TIH w/ o 9902'. C d 2-7/8" tu erk	ing any proposed work. If well is diffectionally drill eker. Welded on 9-5/8" ed up BOP. Tested ars and tubing to 3155'. In Shaw w/BLM with the Lled cement from t 5972'. Drilled cement plug from from 9366-9466'. Washed bit, drill collars and irculated 2-1/2 hours. bing rams. Installed Date June 25, 1993
give substitute to 6-9-93: Du; st: b1 Te BL Wa 46 Ce 83 dc TC tu TC 14. I hereby certify that Signed (This space for Fed Approved by Conditions of approx	g out cellar, cleaned ub with 11" X 3000 sta ind rams to 500 psi, C sted pipe rams to 500 M in Carlsbad about sp shed down to 4650'. T 50-4880'. Washed down ement from 5972-6072'. 800-8415'. Washed down own to 9902'. Circula 00H w/tubing, drill co ubing to 3155'. Rigge 00H w/tubing, drill co " casing rams. The foregoing is true and correct the foregoing is true and correct wal, if any:	location and removed of arting head. Set ancho DK. TIH w/8-3/4" bit, psi, OK. NOTE: Noti- bud. Tagged cement plug at a to 5972'. Tagged ce Washed down to 8300' a to 9366'. Drilled c ted clean. 11ars and bit. Ran loc d up on 6 line. TIH t 11ars and bit. Change 	ry hole mar brs. Nipple drill colla fied Shannor 4650'. Dri ment plug an . Drilled ement plug gs. TIH w/ o 9902'. C d 2-7/8" tu erk	ing any proposed work. If well is diffectionally drill eker. Welded on 9-5/8" ed up BOP. Tested ars and tubing to 3155'. In Shaw w/BLM with the Lled cement from t 5972'. Drilled cement plug from from 9366-9466'. Washed bit, drill collars and irculated 2-1/2 hours. bing rams. Installed Date June 25, 1993
give substitute to 6-9-93: Duy st b1 Te BL Wa 46 Ce 83 dc TC tu TC 14. 1 hereby certify that Signed	g out cellar, cleaned ub with 11" X 3000 sta ind rams to 500 psi, C sted pipe rams to 500 M in Carlsbad about sp shed down to 4650'. T 50-4880'. Washed down ement from 5972-6072'. 800-8415'. Washed down own to 9902'. Circula 00H w/tubing, drill co ubing to 3155'. Rigge 00H w/tubing, drill co " casing rams. The foregoing is true and correct the foregoing is true and correct wal, if any:	location and removed of arting head. Set ancho DK. TIH w/8-3/4" bit, psi, OK. NOTE: Noti- bud. Tagged cement plug at a to 5972'. Tagged ce Washed down to 8300' a to 9366'. Drilled c ted clean. 11ars and bit. Ran loc d up on 6 line. TIH t 11ars and bit. Change 	erk	ing any proposed work. If well is diffectionally drill ther. Welded on 9-5/8" and up BOP. Tested ars and tubing to 3155'. A Shaw w/BLM with the lied cement from t 5972'. Drilled cement plug from from 9366-9466'. Washed bit, drill collars and irculated 2-1/2 hours. bing rams. Installed Date June 25, 1993 Coll Date