

FOLD

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth set
 Adapters—Material Size

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out

TOOLS USED

Rotary tools were used from 0 feet to 9900 feet, and from feet to feet
 Cable tools were used from feet to feet, and from feet to feet

DATES

....., 19..... Put to producing Dry Hole, 19.....

The production for the first 24 hours was barrels of fluid of which% was oil;% emulsion;% water; and% sediment. Gravity, °Bé.

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

J.B. Kelsey Driller Ralph Richardson Driller
R.A. Rogers Driller Driller

FORMATION RECORD

FROM—	TO—	TOTAL FEET	FORMATION
0	250	250	Dolomite
250 -	310	60	Sand
310	1700	1390	Dolomite
1390	2500	1110	Limestone
2500 -	2600	100	Sandstone
2600	2900	300	Dolomite
2900 -	3500	600	Limestone
3500	3930	430	Lmy Sandstone
3930	4750	820	Limestone
4750	5315	565	Sandstone
5315	6805	1490	Limestone
6805	6930	125	Sandstone
6930	7600	670	Shale
7600	8360	760	Limestone
8360	8650	290	Lime, sd, & Sh
8650	8950	300	Limestone
8950	9510	560	Lime, sd, & Sh
9510	9900	390	Sand & Shale

Electronic logs submitted by Welox.

(OVER)

BENTONITE L. & CO. - COLUMBIA

16-43094-5