

Lowest2.txt

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	CLOSURE Distance FT	CLOSURE Direction Deg	Dogleg Severity Deg/100
7723.15	24.33	239.04	7392.24	-825.36	-1375.61	1604.22	1604.22	239.04	.00
7823.15	24.33	239.04	7483.36	-846.56	-1410.93	1645.42	1645.42	239.04	.00
7923.15	24.33	239.04	7574.48	-867.76	-1446.26	1686.61	1686.61	239.04	.00
TOP OF CANYON									
8023.15	24.33	239.04	7665.60	-888.95	-1481.59	1727.81	1727.81	239.04	.00
8123.15	24.33	239.04	7756.72	-910.15	-1516.91	1769.01	1769.01	239.04	.00
8223.15	24.33	239.04	7847.84	-931.34	-1552.24	1810.21	1810.21	239.04	.00
8323.15	24.33	239.04	7938.96	-952.54	-1587.56	1851.40	1851.40	239.04	.00
8423.15	24.33	239.04	8030.08	-973.73	-1622.89	1892.60	1892.60	239.04	.00
8499.89	24.33	239.04	8100.00	-990.00	-1650.00	1924.21	1924.21	239.04	.00
TOTAL DEPTH (BHL 660' FSL & 660' FWL) THESE LINES ARE HARDLINES AND CANNOT BE CROSSED.									

RECEIVED
2001 MAY 25 AM 9:06
BUREAU OF LAND MGMT.
FOSWELL OFFICE