



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Budget Bureau No. 42-10334  
Approval expires 12-31-60.

Land Office Artesia  
Lease No. LC 029309-a  
Unit X

RECEIVED  
OCT 18 1963

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	Subsequent Report of cmtg and testing csg (Cont'd).....

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

*720 survey*  
Well No. 1 is located 560 ft. from S line and 560 ft. from W line of Sec. 24  
SW/4 of Sec. 24 - 20-S - 29-E - NMPN  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Undesignated - Eddy - New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the ~~datum~~ ground above sea level is 3310 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

- June 11, 1963: Ran 9-5/8" csg set @ 3767' w/Baker stage cmt tools set @ 2712' and 1499'. Cmtd w/1095 sks reg reat w/3% Cal. Chl. Did not circ cmt. Top cmt by Temp Survey @ 1375' behind pipe.
- June 12, 1963: Perf 9-5/8" csg @ 1360' and squeeze cmtd w/420 sks 4% gel, 3% Cal. Chl. Circ cmt to surface. WOC 24 hrs. Drilled out cmt and pressure tested perfs - held O.K.
- June 14, 1963: Drilled out DV tool @ 1499' and press tested - held O.K. Drilled out DV tool @ 2712' and press tested - held O.K. Drilled float and press tested - held O.K. Drilled shoe and pressure tested - held O.K.
- Sept 22, 1963: Ran 7" csg set @ 13,104'. Cmtd in two stages:  
1. 400 sks of 50-50 lite poz encore w/3/8# flocele/sk. WOC  
2. 400 sks 50-50 poz encore w/3/8# flocele/sk. WOC.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. (Cont'd)

Company Odessa Natural Gasoline Company

Address Box 3908

Odessa, Texas

Original Signed By  
L. N. Dunnivant

By L. N. Dunnivant

Tide Production Superintendent