IN REPLY REFER TO:



UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY P. O. Drawer U Artesia, New Sexico

RECEIVED MAY 2 8 1963

May 27, 1943 IA, OFFICE

Mr. Perry R. Bass P. O. Sox 1178 Fonshans, Texes

Re: Las Cruces 070227 Expiring Ney 31, 1963

Dear Sir:

Your Notice of Intention to Drill well No. 1 Wright Federal (copy attached) in the SETSW1, sec. 7, T. 20 S., R. 20 M., N.M.P.M., Eddy County, New Maxico to a depth of 1,200 fact to test the Delaware formation is bereby approved subject to compliance with the provisions of the Oil and Gas Operating Regulations and subject to the following conditions:

- 1. Prilling operations so authorized are subject to the attached sheet for general conditions of approval.
- 2. A daily progress report is to be furnished in duplicate from spod date until completion of the well.
- 3. Drilling rig must not be moved from well without prior approval from the Survey (30 GFR 221.3/ic).

Very truly yours,

(Orig. Sigd) RONNIE E. SHOOK

Ronnie E. Shook Acting District Engineer

P.S. If the lease is to be considered for extension by diligent drilling operations, the lease rental must be timely paid.

Form 9-831 a. (Fight 1961)			Budget Bureau No. 42-R358.4. Approval expires 12-31-60.
			Land Office Las Cruces
NEM	(SUBMIT IN	TR IPLIC ATE)	
	UNITED	STATES	Lasse No. 070227
1963	DEPARTMENT O	F THE INTERIOR	Unit
MAY 2	GEOLOGIC	AL SURVEY	
E SHOUNEER	L .		
RONNIE E. ENGINE			
SUNE	DRY NOTICES AND	REPORTS OF	N WELLS
NOTICE OF INTENTION TO D	RILL X	SUBSEQUENT REPORT OF WATER	R SHUT-OFF
NOTICE OF INTENTION TO C		SUBSEQUENT REPORT OF SHOOT	ING OR ACIDIZING
NOTICE OF INTENTION TO T		SUBSEQUENT REPORT OF ALTER	
NOTICE OF INTENTION TO R NOTICE OF INTENTION TO S		SUBSEQUENT REPORT OF RE-DR	
NOTICE OF INTENTION TO P	il i	SUBSEQUENT REPORT OF ABAND SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO A			
	· · · · · · · · · · · · · · · · · · ·		· · · · · · · · · · · · · · · · · · ·
<u></u>	INDICATE ABOVE BY CHECK MARK NATUR	E OF REPORT, NOTICE, OR OTHE	R DATA)
			<u></u>
			ar 24, > & R & B
Wright Federal	,		
Well No. 1 i	is located 660 ft. from s	line and 1980 ft. fr	om willine fly see the
,	(5	J	
SN 1/4 (½ Bec. and Bec. No.)	T-20-S R-28- (Twp.) (Range	E N. M. P. M. (Meridian)	
-Hadant met tod //			Warring Sig
(Field)	County or Subdi	vision)	(State or Territory)
TTI I A' CAL I		* Not ye	t available. Will be
The elevation of the d	lerrick floor above sea level is		ed when rig is moved
	DETAILS C	DF WORK	-
(State names of and expected d	fepths to objective sands; show sizes, weig	hts, and lengths of proposed ca	sings; indicate mudding jobs, cement-
	tepths to objective sands; show sizes, weig ing points, and all other in	portant proposed work)	
It is proposed that a 12" hole to 400; depth with 280 sx.	a well be drilled at t , and setting 8-5/8" OD regular neat cement. A	he above location 24 #/ft. J-55 new fter 24 bra. WOC 1	with cable tools, dril surface casing at that time, casing is to be
It is proposed that a 12" hole to 400', depth with 280 ax. bailed dry, and che	and setting 8-5/8" OD regular neat cement. A cked for fluid entry. (he above location 24 #/ft. J-55 new fter 24 hrs. WOC 1 Cement is to fill	with cable tools, dril surface casing at that time, casing is to be entire annulus to surf
It is proposed that a 12" hole to 400', depth with 280 sx. bailed dry, and che If no fluid enters, a proposed total de J-55 oil string is Completion will be	a well be drilled at t and setting 8-5/8" OD regular neat cement. A ecked for fluid entry. (the plug is to be dril opth of 1200'. Dependin to be run, and cemented made by gun-perforating	he above location 24 #/ft. J-55 new fter 24 hrs. WOC 1 Cement is to fill led, and 7-7/8" ho g on shows encount back to the base	with cable tools, dril surface casing at that time, casing is to be entire annulus to surf ble is to be drilled to tered, $5\frac{1}{2}$ " OD 14 #/ft. of the 3-5/8" OD casin
It is proposed that a 12" hole to 400", depth with 280 sx. bailed dry, and che If no fluid enters, a proposed total de J-55 oil string is Completion will be	a well be drilled at t and setting 8-5/8" OD regular neat cement. A ecked for fluid entry. (the plug is to be dril opth of 1200'. Dependin to be run, and cemented made by gun-perforating	he above location 24 #/ft. J-55 new fter 24 hrs. WOC 1 Cement is to fill led, and 7-7/8" ho g on shows encount back to the base	with cable tools, dril surface casing at that time, casing is to be entire annulus to surf ble is to be drilled to tered, $5\frac{1}{2}$ " OD 14 #/ft. of the 3-5/8" OD casin
It is proposed that a 12" hole to 400", depth with 280 ax. bailed dry, and che If no fluid enters, a proposed total de J-55 oil string is	a well be drilled at t and setting 8-5/8" OD regular neat cement. A ecked for fluid entry. (the plug is to be dril opth of 1200'. Dependin to be run, and cemented made by gun-perforating	he above location 24 #/ft. J-55 new fter 24 hrs. WOC 1 Cement is to fill led, and 7-7/8" ho g on shows encount back to the base	with cable tools, dril surface casing at that time, casing is to be entire annulus to surf ble is to be drilled to tered, $5\frac{1}{2}$ " OD 14 #/ft. of the 3-5/8" OD casin
It is proposed that a 12" hole to 400', depth with 280 sx. bailed dry, and che If no fluid enters, a proposed total de J-55 oil string is Completion will be	a well be drilled at t and setting 8-5/8" OD regular neat cement. A ecked for fluid entry. (the plug is to be dril opth of 1200'. Dependin to be run, and cemented made by gun-perforating	he above location 24 #/ft. J-55 new fter 24 hrs. WOC 1 Cement is to fill led, and 7-7/8" ho g on shows encount back to the base	with cable tools, dril surface casing at that time, casing is to be entire annulus to surf ble is to be drilled to tered, $5\frac{1}{2}$ " OD 14 #/ft. of the 3-5/8" OD casin
It is proposed that a 12" hole to 400", depth with 280 ax. bailed dry, and che If no fluid enters, a proposed total de J-55 oil string is Completion will be fracturing as deeme	a well be drilled at t and setting 8-5/8" OD regular neat cement. A ecked for fluid entry. (the plug is to be dril opth of 1200'. Dependin to be run, and cemented made by gun-perforating	he above location 24 #/ft. J-55 new fter 24 hrs. WOC f Cement is to fill led, and 7-7/8" ho g on shows encount back to the base prospective pay a	with cable tools, dril surface casing at that time, casing is to be entire annulus to surf ble is to be drilled to tered, 51" OD 14 #/ft. of the 3-5/8" OD casin cones, acidizing or
It is proposed that a 12" hole to 400", depth with 280 sx. bailed dry, and che If no fluid enters, a proposed total de J-55 oil string is Completion will be fracturing as deeme	a well be drilled at t and setting 8-5/8" OD regular neat cement. A ecked for fluid entry. (the plug is to be dril opth of 1200'. Dependin to be run, and cemented made by gun-perforating d necessary.	he above location 24 #/ft. J-55 new fter 24 hrs. WOC to Cement is to fill led, and 7-7/8" ho g on shows encount back to the base prospective pay a	with cable tools, dril surface casing at that time, casing is to be entire annulus to surf ole is to be drilled to tered, 5½" OD 14 #/ft. of the 3-5/8" OD casin cones, acidizing or
It is proposed that a 12" hole to 400", depth with 280 ax. bailed dry, and che If no fluid enters, a proposed total de J-55 oil string is Completion will be fracturing as deeme	a well be drilled at t and setting 8-5/8" OD regular neat cement. A ecked for fluid entry. (the plug is to be dril opth of 1200'. Dependin to be run, and cemented made by gun-perforating d necessary.	he above location 24 #/ft. J-55 new fter 24 hrs. WOC f Cement is to fill led, and 7-7/8" ho g on shows encount back to the base prospective pay a	with cable tools, dril surface casing at that time, casing is to be entire annulus to surf ole is to be drilled to tered, 5½" OD 14 #/ft. of the 3-5/8" OD casin cones, acidizing or
It is proposed that a 12" hole to 400", depth with 280 sx. bailed dry, and che If no fluid enters, a proposed total de J-55 oil string is Completion will be fracturing as deeme	a well be drilled at t and setting 8-5/8" OD regular neat coment. A ecked for fluid entry. (the plug is to be dril opth of 1200'. Dependin to be run, and comented made by gun-perforating d necessary.	he above location 24 #/ft. J-55 new fter 24 hrs. WOC to Cement is to fill led, and 7-7/8" ho g on shows encount back to the base prospective pay a	with cable tools, dril surface casing at that time, casing is to be entire annulus to surf ole is to be drilled to tered, 5½" OD 14 #/ft. of the 3-5/8" OD casin cones, acidizing or
It is proposed that a 12" hole to 400', depth with 280 ax. bailed dry, and che If no fluid enters, a proposed total de J-55 oil string is Completion will be fracturing as deeme lunderstand that this plan Company Address Box 1178	a well be drilled at t and setting 8-5/8" OD regular neat cement. A ecked for fluid entry. (the plug is to be dril opth of 1200'. Dependin to be run, and cemented made by gun-perforating d necessary. PERRY R. BASS	he above location 24 #/ft. J-55 new fter 24 hrs. WOC to Cement is to fill led, and 7-7/8" ho g on shows encount back to the base prospective pay a	with cable tools, dril surface casing at that time, casing is to be entire annulus to surf ole is to be drilled to tered, 5½" OD 14 #/ft. of the 3-5/8" OD casin cones, acidizing or
It is proposed that a 12" hole to 400", depth with 280 sx. bailed dry, and che If no fluid enters, a proposed total de J-55 oil string is Completion will be fracturing as deeme	a well be drilled at t and setting 8-5/8" OD regular neat cement. A ecked for fluid entry. (the plug is to be dril opth of 1200'. Dependin to be run, and cemented made by gun-perforating d necessary. PERRY R. BASS	by the Geological Survey befor	with cable tools, drill surface casing at that time, casing is to be entire annulus to surf ole is to be drilled to tered, 5½" OD 14 #/ft. of the 3-5/8" OD casin cones, acidizing or
It is proposed that a 12" hole to 400', depth with 280 ax. bailed dry, and che If no fluid enters, a proposed total de J-55 oil string is Completion will be fracturing as deeme I understand that this plan Company Address Box 1178	a well be drilled at t and setting 8-5/8" OD regular neat cement. A ecked for fluid entry. (the plug is to be dril opth of 1200'. Dependin to be run, and cemented made by gun-perforating d necessary. PERRY R. BASS	he above location 24 #/ft. J-55 new fter 24 hrs. WOC to Cement is to fill led, and 7-7/8" ho g on shows encount back to the base prospective pay 2 by the Geological Survey befor By Malter D	with cable tools, dril surface casing at that time, casing is to be entire annulus to surf ole is to be drilled to tered, 5½" OD 14 #/ft. of the 3-5/8" OD casin cones, acidizing or

. ر

	WEL	NEW MEXICO					FORM C-128 Revised 5/1/57
	SEE II	STRUCTIONS FOR	COMPLETIN	IG THIS FORM O	N THE REVI	ERSE SIDE	
A			SECT Lease				Vell No.
Operator	PERRY R. BA	SS	Lerie		T FEDE	RAL	1
Unit Letter	Section	Township		Lage	County		
N Actual Footoga	7 Location of Vell:	20 SOUTH	2	28 EAST	1	E	DDY
660	feet from the	SOUTH lie	e aad	1980 fee	t from the	WEST	line
Ground Level E	lev. Producing I	ormation	Pool	18.5		····	Dedicated Acreage:
3304.1	Net	unand _		we			Acres
	NO r to question two is PERRY 8, 3431				erests below:		
· · · · · · · · · · · · · · · · · · ·		SECTION B		- <u> </u>	······································]	CERTIFICATION
				RECEIVED	ARTESIA, NEW MEXICO	in SECTI plete to the belief. Name Position Asei Company Post Date	certify that the information ON A above is true and com- he best of my knowledge and Man Anne Cant Dive Ngre Tr R. Base
						I harahu .	ertify that the well location
				676	SURVEYO	shown on plotted fr surveys a supervisi	the plat in SECTION B was om field notes of actual nade by me or under my on, and that the same is true of to the best of my knowled, f.
	980'		15-21	GATE ON	SURVEYO	shown on plotted fr surveys a supervisi and corre and belie Date Surv Registe re	om field notes of actual node by me or under my on, and that the same is true ct to the best of my knowled f.