

Form 9-331a  
(Feb. 1951)Budget Bureau No. 42-B358.4.  
Approval expires 12-31-60.

(SUBMIT IN TRIPLICATE)

Land Office **Las Cruces**Lease No. **070227**

Unit

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYRECEIVED  
JUN 17 1963

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 12, 1963

## Wright Federal

Well No. **1** is located **660** ft. from **S** line and **1980** ft. from **W** line of sec. **7**SW 1/4 of sec. **7**

(1/4 Sec. and Sec. No.)

T-20-S

(Twp.)

R-28-E

(Range)

N. M. P. M.

(Meridian)

Undesignated

(Field)

Eddy

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is **3305** ft. Ground level elev: **3304** ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

After setting the 7" casing at 418' on a shoulder, as previously reported, encountered water while drilling from 418' to 425'. Spudded 7" casing down to 425' and shut off the water. Encountered top of salt at 480', top of Yates at 730'. Reached total depth of 1048' as of 1:45 p.m. 6-12-63. Schlumberger ran gamma ray and neutron log. Top of Seven Rivers by log 1032'. Hole filled up with black sulphur water from bottom to 810' after making the last 4' of hole. Preparing to pull casing, plug and abandon.

As per telephone conversation with Mr. Brown this date, we propose to plug and abandon the well in the following manner. Pull 7" and 8-5/8" casing strings. Hole will be mudded from top to bottom. Spot 100' cement plug on bottom. Spot 100' cement plug 480-600' to straddle base of Salt at 522'. Spot 100' cement plug 150-250'. Spot 25' cement plug at top of hole. Install marker & sign, clear location.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **PERRY R. BASS**Address **Box 1178****Monahans, Texas**

By

Title

**Walter D. Powers**  
**Asst. Div. Manager**