S SUBMIT IN TR (Other Instruction INTERIOR verse side)	CATE Porm approv CATE Bure Budget Bure CB TY 5. LEASE DESIGNATION LC 072015-C	au No. 43-181424.
a or plug back to a different reaervol for such propasals.)	ir	
RECEIV	ED	
NOV 29 19	76 Hanson-Fede	
ARTESTA, NEW N	SURVEY 1 IEXICO Avalon (Mor 11. and T. B. M. OR BURYBY OR ARM	T-20-S, R-27-
	Eddy	New Mexico
dicate Nature of Notice, Repo I	ort, or Other Data accasecent apport of:	
(Other) Recomp (Note: Repo Completion of	ZING ABANDON MA Detion in Morrow rt results of multiple completion r Recompletion Report and Log for	ABING
	Whether DF. HT. CR. etc.) 3246 KB dicate Nature of Notice, Republic Water SHUT-OFF Fracture SHUT-OFF Completion of Second Completion of Second Comp	S SUBMIT IN TR (Other Instruction of Program approximation RVEY ORTS ON WELLS a or plug back to a different reservoir. for such proposals.) RECEIVED NOV 29 1976 US GEOLOGICAL SURVEY with any State requirement NEW MEXICO ARTESTA, NEW MEXICO ARTESTA, NEW MEXICO Section 34, 12. COUNTY OR PARAMAN Section 34, 12. COUNTY OR PARAMAN Section 34, 13. COUNTY OR PARAMAN Section 34, 13. COUNTY OR PARAMAN Section 34, 14. Sector Prover, or Other Dote SUBARCENT REPORT OF: WATER SHUT-OFF FRACTURE TREATMENT

1. DESCRIPTION WORK. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and measured and true vertical depths for all markers are presented to this work.)^a

RU well service unit; killed well with 10.0 ppg brine; pulled tubing with packer. Set cement retainer at 9520' -- squeezed perfs 9637' to 9653' with 3 stages cement (1st stage 100 sx Class "H"; 2nd stage 50 sx Class "H"; 3rd stage 50 sx Class "H") attained 3500 psi squeeze pressure and held on 3rd stage. Drilled cement retainer at 9520' and hard cement 9520' to 9654' -- pressure tested squeezed interval to 1500 psi without loss. Ran bit to 11,100' and reversed out mud. POH with bit -- ran CR-CBL log from 11,000' to 9000'. WIH with Baker model "R" double grip packer on 2 3/8" tubing. Ran bottom of tubing to 10,959' and displaced hole with 9.2 ppg packer fluid (3% KC1, 1% Champion #2264) -spotted 250 gals 10% acetic acid 10,959' to 10,699'. Set packer at 10,621', bottom of tubing at 10,658'. Swabbed fluid level down to 8000' for underbalanced condition. Perforated with three tubing gun as follows: (1 shot at each point) 10,866 1/2', 10,868', 10,868 1/2', 10,913', 10,913 1/2', 10,920', 10,920 1/2', 10,922', 10,922 1/2', 10,948, 10,948 1/2', 10,950', 10,950 1/2', 10,952', 10,952 1/2', 10,954', 10,954 1/2' (total of 17 holes). Had 1000 psi on well head after perforating. Opened well to pit and flowed to clean up 3 hours. Closed well in for build up November 11, 1976. Completion date: November 11, 1976.

Conducted CAOF test November 17, 1976 -- CAOF 2560 MCFPD.

Well closed in waiting on sales connection.

18. I hereby certify that the foregoing is DATE November 24. 1976 Manager-Engineer TITLE SIGNED This space for Federal or State TITLE ACTING DISTRICT ENGINEER 1976 DATE DEC 6 APPROVED BY APPROVAL, IF ANY : CONDITIONS OF

*See Instructions on Reverse Side