

6. RU. WIRELINE. RUN GRUCL & CORRELATE TO ATTACHED ALEX ACOUSTIC VELOCITY LOG DATED 11-20-63 & PERF W/4" HSC CSG GUN AS FOLLOWS:

(7304-7310)	6'	4JSPF	24 HOLES	IF POSSIBLE
(7356-7364)	8'	4JSPF	32 HOLES	IF NECESSARY
TOTALS	14'		56 HOLES	

7. PICK UP & RIH W/5-1/2" BKR MOD "R" PKR, API SN, ON 2-7/8" 6.5# J-55 TBG. SET PKR @ 7282' W/15000# COMPRESSION. ND WELLHEAD. NU WELLHEAD.

8. RU HOWCO. LOAD BACKSIDE W/2% KCL WTR & TRAP 500 PSI. SET CSG POP OFF VALVE @ 1000 PSI. ACDZ PERFS (7304-7450) W/3200 GALS 15% FE HCL FOAMED W/N₂ TO 75% QUALITY @ 3 BPM MAX PRESSURE = 3500 PSI AS FOLLOWS:

- A. 200 GALS 15% FE HCL
- B. 5000 GALS 75% FOAMED 15% FE HCL
- C. 2000 GALS 75% FOAMED 15% FE HCL W/1 #/GAL TBA-110 (RS)
- D. 5000 GALS 75% FOAMED 15% FE HCL
- E. FLUSH W/±25000 SCF N₂
- F. OBTAIN ISIP, 5 MIN, 10 MIN, 15 MIN SIP
- G. OPEN WELL FLOW TO FRAC TANK REC LOAD
- H. SWITCH WELL TO PROD UNIT

SUMMARY:

3200 GALS 15% FE HCL
255,000 SCF N₂ (INCLUDING COOLDOWN)
2000 LBS. TBA-110 ROCK SALT

ADDITIVES:

15% FE HCL	- 5 GALS/M PEN-5
	- 2 GALS/M HAI-65
ROCK SALT	- 1 LB/GAL IN 1000 GALS FOAM

9. RR.