

**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

RECEIVED

OCT 22 1963

URGENT NOTICES AND REPORTS ON WELLS. C. C.

[illegible]

SECRET

_____ 1963

Well No. 2 is located 660 ft. from W line and 1983 ft. from W line of sec. 17

~~SECRET~~

The elevation of the darkest floor above sea level is 1244.2 ft.

DETAILS OF WORK

[illegible]

10- 6-44- Sat. 1944 of 13-2/3", H-40, 1000 soaking w/ 1000 sacks except (200 sacks
 inner for 1000 gal and 200 GMI plus 1000 sacks inner w/ 1000 GMI). Tested
 eng w/ 1000 for 30 min. - held strong. WBS 10 hours.

[illegible]

2) Run Temperature survey. Found top of cement at approx. 375'. *over*

24. ~~Indicate whether regular contact w/ [redacted] last back side of 9-5/8"~~ *one*

I understand that this plan of work must be approved by the National Security before operations may be commenced.

Company - **AMERICAN L. B. WOOD**

Address _____

Lesson 11. New Mexico

By H. LEE HARVARD
 Title Oncologist - Engineer

- 3) Pumped 110 sacks regular cement w/ 2% CaCl₂
down back side of 9 5/8" casing thru 1" line pipe
Cement circulated, then fell back to 30' of surface
- 4) filled up to surface w/ 10 sacks cement
Put in from surface.
- 5) woc 24 hrs.