Form 9-331 a (Feb. 1951)

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY** 

Land Office	em Hex100						
Lease No. 14-040781							
Unit	n a						

SUNDRY NOTICES AND REPORTS ON WEL

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.	SUBSEQUENT REPORT OF ABANDONMENT.
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

		*	June 3, 196	53	, 19
ell No. 1-A is located	1220 ft. from	$n = \{N\}$ line and	660 ft. from	$\mathbb{E}$ line of se	c. <u>35</u>
4 35 /4 300 35	27 8	<b>21</b>	<b>Унри</b>		
(¼ Sec. and Sec. No.)	(Twp.)	(Range)	(Meridian)		
dfirch Area allicat	sade			w Mexico	
(Field)	(County	or Subdivision)		(State or Territory)	
dfirch Area wildost	(TWP.)	or Subdivision)	(Meridian)	State or Territory)	

The elevation of the derrick floor above sea level is 4650 ft. est.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Ran 1206' of 7-5/8" (24s, 8-40) desing and cemented \$ 1206' with 300 manks regular neat plus 2% CaCl2 and 1/4% flo seal per sack. Left 903' of cament in casing. Plug down w 6:30 a.m. (MOT), May 23, 1963. After mot 23 hours, tested with 1000 psi for 30 minutes - no pressure drop.

I understand that this plan of work must receive approval in writing by the Geological Survey before of Shell (dl Company Company .... Box 1858 Address \_\_\_\_ Morwell, for hexico Title Must on Bechard cal Engineer