

FHP 7063.

6-4-64 TD - 13,020, DST No. 12 - 12,872' to 13,020'. Tool open 2½ hrs. with fair blow
rec. 1600' water cushion. 720' drilling mud, 9,680' salt water 14,000 PPM,
LHP - 7171, ISIP - 60 Min. 5875, LFP - 1620, FFP - 5594, FSIP 60 min. 5875,
FHP-7128.

6-6-64 TD, 13,020. Finished logging well.

6-7-64 TD - 13,020, P & A. Plugs set as per Mr. Beekman instruction as follows:

12,500' to 12,600'	50 sx plug
11,000' to 11,100'	50 sx plug
9,300' to 9,500'	200 sx plug
7,700' to 7,800'	50 sx plug
6,100' to 6,200'	50 sx plug
4,800' to 4,900'	50 sx plug
3,150' to 3,250'	50 sx plug
10 sx in top of 9 5/8" casing with regular marker.	

Sample tops are as follows:

Bone Spring	5,890'
1st Bone Springs Sand	7,180'
2nd Bone Springs Sand	8,010'
3rd Bone Springs Sand	8,910'
Wolfcamp	9,440'
Pennsylvania	10,226'
Lower Strawn	10,500'
Atoka	10,942'
Lower Marrow	11,500'
Upper Mississippian	11,869'
Lower Mississippian	12,286'
Woodford	12,760'
Devonian	12,840'

RECEIVED

JUN 15 1964

O. C. C.
ARTEBIA, OFFICE

RECEIVED
JUN 15 1964
ARTEBIA, OFFICE