

NO. OF COPIES RECEIVED	6
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	4

**RECEIVED**

NEW MEXICO OIL CONSERVATION COMMISSION

JUN 12 1968

**O. C. C.**  
ARTESIA, OFFICE

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease  
State  Fee

5. State Oil & Gas Lease No.

**SUNDRY NOTICES AND REPORTS ON WELLS**

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input checked="" type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator <b>HARVEY E. YATES</b>	8. Farm or Lease Name <b>Hondo Singer "A"</b>
3. Address of Operator <b>112 No. First Street Artesia, New Mexico</b>	9. Well No. <b>1</b>
4. Location of Well UNIT LETTER <b>P</b> <b>660</b> FEET FROM THE <b>South</b> LINE AND <b>660</b> FEET FROM <b>East</b> LINE, SECTION <b>7</b> TOWNSHIP <b>20 S</b> RANGE <b>27 E</b> NMPM.	10. Field and Pool, or Wildcat <b>McMillan Morrow Gas</b>
15. Elevation (Show whether DF, RT, GR, etc.)	12. County <b>Eddy</b>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

We propose to P & A in the following manner:

Set a 100' cement plug from 8674 - 8574; knock off 5 1/2" csq; place a 100' cement plug at stub; place a 100' cement plug from 5300 - 5400; place a 100' cement plug across the shoe of the 9 5/8" csq 2907 - 3007'; and place plug at surface with Reg. Dry hole marker. Hole will be mudded between plugs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Harvey E. Yates TITLE Operator DATE June 10, 1968

APPROVED BY W.A. Gressett TITLE OIL AND GAS INSPECTOR DATE June 10, 1968

CONDITIONS OF APPROVAL, IF ANY: Notify N.M.O.C.C. in sufficient time to witness plugging