

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Hondo Oil & Gas Co.</i>		Lease <i>Hondo Singer "C"</i>		Well # <i>1</i>	
Location of Well	Unit <i>1980N+W</i>	Section <i>18</i>	Township <i>20</i>	Range <i>27</i>	County <i>Eddy</i>
Drilling Contractor <i>Castro & Corp.</i>		Type of Equipment <i>Rotary</i>			
APPROVED CASING PROGRAM <i>8600 w.c. or less</i>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17 1/2</i>	<i>13 3/8</i>	<i>48 #</i>	<i>New</i>	<i>350</i>	<i>Circulate</i>
<i>12 1/4</i>	<i>9 5/8</i>	<i>32.3+36</i>	<i>New</i>	<i>2950</i>	<i>11</i>
<i>8 3/4</i>	<i>5 1/2</i>	<i>14 15.5+17</i>		<i>8700'</i>	<i>300</i>
Casing Data:					
Surface <i>26.00</i> joints of <i>26.00</i> inch <i>26.00</i> # Grade <i>New</i>					
(Approved) (Rejected)					
Inspected by <i>L. J. ...</i> date <i>5-19-64</i>					
Cementing Program					
Size of hole <i>12 1/4</i> Size of Casing <i>9 5/8</i> Sacks cement required <i>150</i>					
Type of Shoe used <i>1 1/2</i> Float collar used <i>2</i> Btm 3 jts welded <i>2</i>					
TD of hole <i>211</i> Set <i>258</i> Feet of <i>12 1/4</i> Inch <i>30</i> # Grade <i>New</i>					
New-used csg. @ <i>2469</i> with <i>150</i> sacks neat cement around shoe					
+ <i>100</i> sacks <i>100</i> gel additives <i>100</i>					
Plug down @ <i>8:00</i> (AM) (PM) Date <i>5-19-64</i>					
Cement circulated <i>yes</i> No. of Sacks <i>150</i>					
Cemented by <i>H. J. ...</i> Witnessed by <i>L. J. ...</i>					
Temp. Survey ran @ <i>2:00</i> (AM) (PM) Date <i>5-20-64</i> top cement @ <i>2:00</i>					
Casing test @ <i>2:00</i> (AM) (PM) Date <i>5-20-64</i>					
Method Used <i>...</i> Witnessed by <i>...</i>					
Checked for shut off @ <i>2:00</i> (AM) (PM) Date <i>5-20-64</i>					
Method used <i>...</i> Witnessed by <i>...</i>					
Remarks: <i>100 sacks 100 gel additives 100</i>					
<i>to pressure up @ 2:00 PM, 5-20-64</i>					
<i>Checked by M.L.C.</i>					