

MARTHA CREEK :#1
INDIAN EASTIN
EDDY COUNTY, NEW MEXICO
S30-T21S-R24E

WELL SCHEMATIC

CASING	Size	Weight	Grade	Thread	Depth
CASING	9-5/8	36	J-55		2002
CASING	7"	23 & 26	J-55, N-80		9522
TUBING	2-3/8	4.7	H-55	Hydril	7272
TUBING	2-3/8	4.7	J-55	8RD EUE	9111
DESCRIPTION OF EQUIPMENT					DEPTH
13-3/8" 48# H-40 cemented with 250 sxs					198'
TOC at 90' from surface					
LS - East side					
SS - West side 2-3/8" Hydril IPC with Tk-2					
of tubing					
* HOLE IN LONG STRING $C \pm 3200'$ *					
9-5/8 36# J-55 cemented with 1575 sxs					2002'
TOC at surface by 1" Top Job					
7" CSA cemented with 400 sxs					9522
TOC by CBL at 6850'					
DV tool - No record of 2nd stage cement					7280'
Model 'K' snapset single grip packer set by LS					7276'
14M# weight by SS					
Cisco (U. Penn) Perfs 7334-59'					
7364-94'					
7422-44'					
Baker model 'N' bridge plug, set on 10-21-87					
Baker Model 'D' (WLS) 6M# weight by LS					9095'
5' production tube with 1/2" welded pin					
Morrow perfs - 9152-62', 9224-38', 9318-34',					
9352-60', 9396-9406', 9418-26'					
PBTB - 9471'					TD 9522'

Prepared by
F. Gregg Jacob

Date
October 6, 1987

