

Land Office New Mexico
Lease No. NM 063744
Unit F

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

APPROVED
X
DEC 30 1963
RONNIE E. SHOOK
ACTING DISTRICT ENGINEER

SUNDRY NOTICES AND REPORTS ON WELLS

| | | | |
|--|---|--|---|
| NOTICE OF INTENTION TO DRILL | X | SUBSEQUENT REPORT OF WATER SHUT-OFF | RECEIVED DEC 31 1963 O. C. C. ARTESIA, OFFICE |
| NOTICE OF INTENTION TO CHANGE PLANS | | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING | |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | | SUBSEQUENT REPORT OF ALTERING CASING | |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR | |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | | SUBSEQUENT REPORT OF ABANDONMENT | |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | | SUPPLEMENTARY WELL HISTORY | |
| NOTICE OF INTENTION TO ABANDON WELL | | | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Marathon-Federal December 26, 1963

Well No. 1 is located 1650 ft. from N line and 1650 ft. from W line of sec. 28
SE 1/4 NW 1/4 Sec 28 22-S 23-E NMPM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat Eddy New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the ~~derrick floor~~ GL above sea level is 4254 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We plan to drill a Morrow Sand Gas Test to 10,000'.
Will run approximately 100' of 13 3/8" Surface Casing Cemented to Surface. Approximately 1400' of 9 5/8" 36# Casing Cemented to Surface or tie into surface string. app. 9800' of 7" 26# Casing Cemented with sufficient Cement.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Ralph Lowe

Address Box 832

Midland, Texas

By [Signature]

Title agent