

FOL

Reaming plug—Material Length Depth set

Adapters—Material Size

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleared out

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet

Cable tools were used from feet to feet, and from feet to feet

DATES

....., 19..... Put to producing , 19.....

The production for the first 24 hours was barrels of fluid of which% was oil;% emulsion;% water; and% sediment. Gravity, °Bé.

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

J. J. Boyad , Driller G. W. Millard , Driller
B. J. Boyad , Driller , Driller

FORMATION RECORD

FROM—	TO—	TOTAL FEET	FORMATION
0	590	590	Sand & Dol.
590	1400	810	Dolomite
1400	2065	665	Limestone
2065	2830	765	Sand & Dol.
2830	3670	840	Sand & Ls.
3670	4840	2620	Limestone
4840	6635	335	Sand & Ls.
6635	7600	975	Shale & Ls.
7600	7750	150	Limestone
7750	8075	225	Lime & Shale
8075	8275	300	Shale, Sd, & Ls
8275	8510	235	Limestone
8510	8715	205	Limestone, Shale, & Sd

RECEIVED
MAR 4 1964
U. S. GEOLOGICAL SURVEY
ARTESIAN, NEW MEXICO

[OVER]