

U. S. G. O. COPY

INFORMATION COPY

(SUBMIT IN TRIPLICATE)

Budget Bureau No. 42-R358.4.
Form Approved.Land Office New MexicoLease No. NM 063744Unit F

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Copy to J. F.
to

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	X
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Marathon-FederalMarch 5, 1964Well No. 1 is located 1650 ft. from N line and 1650 ft. from E line of sec. 28
SE 1/4 NW 1/4 Sec. 28 22-S 23-E NMPM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat (marrow) Eddy New Mexico
(Field) (County or Subdivision) (State or Territory)
GLThe elevation of the ~~derrick floor~~ above sea level is 4254 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Well Plugged per instructions USGS as follows: 40 sacks
 Cement - 10,000' - 10'100'. 40sack 9370' - 9470', 40sack 8830' - 8930'.
 40sack 7550' - 7650', 40sack 6500' - 6600', 40sack 4440' - 4500',
 40sack 2450' - 2550', 40sack 1400' - 1500', 25sacks in Top
 9 5/8" Casing with 4' Marker, Good oil base Mud used
 between Cement Plugs.

RECEIVED

APR 6 1965

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Ralph LoweAddress Box 832Midland, TexasBy E. J. MurrayTitle agent