

- 8-9-64: DST #4 - 7615-7665', tool opened with strong blow, GTS in 3 minutes, MTS in 30 minutes. TO 2 hrs & 12 minutes on 5/8" bottom choke, 1" top choke to 1/4" choke on last hour of flow - 1325 psi on 1/4". Water to surface in 43 minutes. Flowed 1750 MCFPD before fluid hit, flowed @ 800 psi surface press. Recovered 1500' (16 bbls.) black sulphur water, water/oil ratio 326/1MM. 32 min ISIP-2931, 2 hr & 13 min FSIP-2931, IF-2750, I&FHP-3748.
- 8-16-64: DST #5 - 8425-50', Lower Strawn. TO 46 minutes weak blow 10 minutes and died. Recovered 5 gal. mud. I&FHP-4110, 1 hr ISIP-138, IFP-92, FFP-92, 90 min FSIP-140.
- 8-20-64: DST #6 - 8762-8805', Atoka sand, ;tool open 1 hr & 12 minutes. Good blow through out. GTS in 17 min, TSTM. Recovered 180' GCM, 3/4" bottom choke, 1/8" top choke. IHP-4244, 1 hr ISIP-3022, FP-92-138, 2 hr FSIP-3294 (still building), FHP-4244.
- 8-26-64: DST #7 - 9240-9303', GTS in 5 minutes, 250 MCFPD rate. Surface pressure-26 psi, tool open 1 hr & 38 minutes, 3/4" bottom choke and 1/2" top choke. Recovered 350' GCM. 60 min ISIP-3521, IFP-138, FFP-185, 2½ hr FSIP-3702.
- 8-28-64: DST #8 - 9341-9400', tool open 1 hr & 32 minutes @ final flow rate of 425 MCFPD. 1 hr ISIP-3793, IFP-138, FFP-185, 2 hr FSIP-3793. Recovered 325' HGCM - flow rate climbed gradually during test.
- 8-29-64: DST #9 - 9395-9440', tool open 67 minutes, 3/4" bottom choke, GTS in 5 minutes, 1/2" top choke. Rate 240 MCFPD, recovered 80' GCM. 60 min ISI-3476, IF-93, FF-139, 60 min FSI-3793, I&FHP-5008.
- 8-31-64: DST #10 - 9441-9575' Morrow. Tool open 91 minutes, GTS in 5 minutes, stabilized flow rate at end of test 672 MCFPD. Recovered 230' GCM. 1 hr ISIP-3839, IFP-231, FFP-231, 1½ hr FSIP-3884.

RECEIVED

OCT 13 1964

O. C. C.
ARTESIA, OFFICEXERO
COPYXERO
COPY