N. M. O. C. C. CO	Budget Bureau No. 42-R358.4 Approval expires 12-31-60.
Form 9-331 a (Feb. 1951)	Land Office Xinth New M
(SUBMIT IN TR	(IPLICATE) Lease No. 1.C063246.D
UNITED S	TATES K
DEPARTMENT OF GEOLOGICAL	Se sine that he I V L
A THEFT	DEC 2 4 1964
ALTING CUNDRY NOTIOES AND	DEDODTS ON WELLS
SUNDRY NOTICES AND	REPORTS ON WELLS. C. C.
NOTICE OF INTENTION TO DRILL	BSEQUENT REPORT OF WATER SHUT-OFF
	BSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF SUB	BSEQUENT REPORT OF ALTERING CASING
	BSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO PULL OR ALTER CASING	PPLEMENTARY WELL HISTORY
(INDICATE ABOVE BY CHECK MARK NATURE C	OF REPORT, NOTICE, OR OTHER DATA)
	10
	December 11, 19.4
Winston-Federal	
Well No. <u>1</u> is located 2080 ft. from $\begin{cases} N \\ S \end{cases}$ 1	line and $\frac{1765}{100}$ ft. from $\{\overline{W}\}$ line of sec. 31
NE/4 SW/4 21S 24E	E NMPM
(½ Sec. and Sec. No.) (Twp.) (Range)	(Meridian)
Indian Basin - Upper Penn. Gas Eddy (Field) (County or Subdivisi	sion) (State or Territory)
The elevation of the derrick floor above sea level is 3	
DETAILS OF	
State names of and expected depths to objective sands; show sizes, weight ing points, and all other impo	ortant proposed work)
TO THE TEL THAT THE ALL ORDAN SHI MALINA	abala DST#2 9390-9483 GTS 1:5
Drilled 6-3/4" hole to 9730 ' in Barnett	
Rec. 1900' salt water. FSIP 3713. DST	T#3 9544-9730 GTS :04 10900 MCF
Rec. 1900' salt water. FSIP 3713. DST 140' water. FSIP 3637. Ran 54 joints	T#3 9544-9730 GTS :04 10900 MCF s of 4-1/2" pipe as liner set @ 9730'
Rec. 1900' salt water. FSIP 3713. DST 140' water. FSIP 3637. Ran 54 joints and comented with 175 sacks. Set for	T#3 9544-9730 GTS :04 10900 MCF s of 4-1/2" pipe as liner set (9730' 24 hours and tested to 3000#. Perfo
Rec. 1900' salt water. FSIP 3713. DST 140' water. FSIP 3637. Ran 54 joints and comented with 175 sacks. Set for 9432-48 and swabbed 8 barrels of wate	T#3 9544-9730 GTS :04 10900 MCF is s of 4-1/2" pipe as liner set (9730' 24 hours and tested to 3000#. Perfo er 12 hours. Squeezed perforations 9
Rec. 1900' sait water. FSIP 3713. DST 140' water. FSIP 3637. Ran 54 joints and commented with 175 sacks. Set for 9432-48 and swabbed 8 barrels of wate with cement to 6000#. Perforated 9545	T#3 9544-9730 GTS :04 10900 MCF is s of 4-1/2" pipe as liner set (9730' 24 hours and tested to 3000#. Perfo er 12 hours. Squeezed perforations 9 5-47; 9584-86 and 9601-04. Morrow
Rec. 1900' salt water. FSIP 3713. DST 140' water. FSIP 3637. Ran 54 joints and commented with 175 sacks. Set for 9432-48 and swabbed 8 barrels of wate with cement to 6000#. Perforated 9545 completed natural 6000 MCF COAF. Performent.	T#3 9544-9730 GTS :04 10900 MCF is s of 4-1/2" pipe as liner set (9730' 24 hours and tested to 3000#. Perform r 12 hours. Squeezed perforations 9 5-47; 9584-86 and 9601-04. Morrow erforated 7476-94 and acidized with 5
Rec. 1900' sait water. FSIP 3713. DST 140' water. FSIP 3637. Ran 54 joints and commented with 175 sacks. Set for 9432-48 and swabbed 8 barrels of wate with cement to 6000#. Perforated 9545	T#3 9544-9730 GTS :04 10900 MCF is s of 4-1/2" pipe as liner set (9730' 24 hours and tested to 3000#. Perform r 12 hours. Squeezed perforations 9 5-47; 9584-86 and 9601-04. Morrow erforated 7476-94 and acidized with 5
Rec. 1900' salt water. FSIP 3713. DST 140' water. FSIP 3637. Ran 54 joints and commented with 175 sacks. Set for 9432-48 and swabbed 8 barrels of wate with cement to 6000#. Perforated 9545 completed natural 6000 MCF COAF. Per	T#3 9544-9730 GTS :04 10900 MCF is s of 4-1/2" pipe as liner set (9730' 24 hours and tested to 3000#. Perform r 12 hours. Squeezed perforations 9 5-47; 9584-86 and 9601-04. Morrow erforated 7476-94 and acidized with 5
Rec. 1900' salt water. FSIP 3713. DST 140' water. FSIP 3637. Ran 54 joints and commented with 175 sacks. Set for 9432-48 and swabbed 8 barrels of wate with cement to 6000#. Perforated 9545 completed natural 6000 MCF COAF. Per	T#3 9544-9730 GTS :04 10900 MCF is s of 4-1/2" pipe as liner set (9730' 24 hours and tested to 3000#. Perform r 12 hours. Squeezed perforations 9 5-47; 9584-86 and 9601-04. Morrow erforated 7476-94 and acidized with 5
Rec. 1900' salt water. FSIP 3713. DST 140' water. FSIP 3637. Ran 54 joints and comented with 175 sacks. Set for 9432-48 and swabbed 8 barrels of wate with cement to 6000#. Perforated 9542 completed natural 6000 MCF COAF. Pe gallons. Cisco completed for 29000 1	T#3 9544-9730 GTS :04 10900 MCF is s of 4-1/2" pipe as liner set (9730' 24 hours and tested to 3000#. Perforentiations 9 to 12 hours. Squeezed perforations 9 5-47; 9584-86 and 9601-04. Morrow erforated 7476-94 and acidized with 5 MCF CAOF.
Rec. 1900' salt water. FSIP 3713. DST 140' water. FSIP 3637. Ran 54 joints and commented with 175 sacks. Set for 9432-48 and swabbed 8 barrels of wate with cement to 6000#. Perforated 9545 completed natural 6000 MCF COAF. Per	T#3 9544-9730 GTS :04 10900 MCF s of 4-1/2" pipe as liner set (9730' 24 hours and tested to 3000#. Perfo er 12 hours. Squeezed perforations 9 5-47; 9584-86 and 9601-04. Morrow erforated 7476-94 and acidized with 5 MCF CAOF.
Rec. 1900' salt water. FSIP 3713. DST 140' water. FSIP 3637. Ran 54 joints and comented with 175 sacks. Set for 9432-48 and swabbed 8 barrels of wate with cement to 6000#. Perforated 9545 completed natural 6000 MCF COAF. Pe gallons. Cisco completed for 29000 1	T#3 9544-9730 GTS :04 10900 MCF s of 4-1/2" pipe as liner set 9730' 24 hours and tested to 3000#. Perfo er 12 hours. Squeezed perforations 9 5-47; 9584-86 and 9601-04. Morrow erforated 7476-94 and acidized with 9 MCF CAOF.
Rec. 1900' salt water. FSIP 3713. DST 140' water. FSIP 3637. Ran 54 joints and comented with 175 sacks. Set for 9432-48 and swabbed 8 barrels of wate with cement to 6000#. Perforated 9545 completed natural 6000 MCF COAF. Pe gallons. Cisco completed for 29000 1	T#3 9544-9730 GTS :04 10900 MCF s of 4-1/2" pipe as liner set 9730' 24 hours and tested to 3000#. Perfo er 12 hours. Squeezed perforations 9 5-47; 9584-86 and 9601-04. Morrow erforated 7476-94 and acidized with 9 MCF CAOF.
Rec. 1900' salt water. FSIP 3713. DST 140' water. FSIP 3637. Ran 54 joints and comented with 175 sacks. Set for 9432-48 and swabbed 8 barrels of wate with cement to 6000#. Perforated 9542 completed natural 6000 MCF COAF. Pe gallons. Cisco completed for 29000 1	T#3 9544-9730 GTS :04 10900 MCF s of 4-1/2" pipe as liner set (9730' 24 hours and tested to 3000#. Perfo er 12 hours. Squeezed perforations 9 5-47; 9584-86 and 9601-04. Morrow erforated 7476-94 and acidized with 5 MCF CAOF. How the Geological Survey before operations may be commenced.
Rec. 1900' salt water. FSIP 3713. DST 140' water. FSIP 3637. Ran 54 joints and comented with 175 sacks. Set for 9432-48 and swabbed 8 barrels of wate with cement to 6000#. Perforated 954! completed natural 6000 MCF COAF. Pe gallons. Cisco completed for 29000 1 I understand that this plan of work must receive approval in writing b Company <u>Redfern Development Corporation</u>	T#3 9544-9730 GTS :04 10900 MCF s of 4-1/2" pipe as liner set (9730' 24 hours and tested to 3000#. Perfo er 12 hours. Squeezed perforations 9 5-47; 9584-86 and 9601-04. Morrow erforated 7476-94 and acidized with 5 MCF CAOF. How the Geological Survey before operations may be commenced.
Rec. 1900' salt water. FSIP 3713. DST 140' water. FSIP 3637. Ran 54 joints and comented with 175 sacks. Set for 9432-48 and swabbed 8 barrels of wate with cement to 6000#. Perforated 954! completed natural 6000 MCF COAF. Pe gallons. Cisco completed for 29000 1 Iunderstand that this plan of work must receive approval in writing b Company <u>Redfern Development Corporation</u>	T#3 9544-9730 GTS :04 10900 MCF s of 4-1/2" pipe as liner set (9730' 24 hours and tested to 3000#. Perfo er 12 hours. Squeezed perforations 9 5-47; 9584-86 and 9601-04. Morrow erforated 7476-94 and acidized with 5 MCF CAOF. How the Geological Survey before operations may be commenced.
Rec. 1900' salt water. FSIP 3713. DST 140' water. FSIP 3637. Ran 54 joints and comented with 175 sacks. Set for 9432-48 and swabbed 8 barrels of wate with cement to 6000#. Perforated 954! completed natural 6000 MCF COAF. Pe gallons. Cisco completed for 29000 1 Iunderstand that this plan of work must receive approval in writing b Company Redfern Development Corporation	T#3 9544-9730 GTS :04 10900 MCF s of 4-1/2" pipe as liner set (9730' 24 hours and tested to 3000#. Perfo er 12 hours. Squeezed perforations 9 5-47; 9584-86 and 9601-04. Morrow erforated 7476-94 and acidized with 9 MCF CAOF.