

WELL DIAGRAM BEFORE WORKOVER

DIAGRAMATIC SKETCH OF DUAL GAS COMPLETION
Winston - I

13 3/8" O.D. 48# H-40 Casing
Set at 320'
Cemented to Surface W/700 sx. in Six Stages.

11 1/8" O.D. 48# H-40 Casing Set at 1700'
Cemented W/640 sx. 8% gel 150 sx. neat.
Plus 175 sx. in Three Stages. - Cement to Surface.

Top Cement @ 5230' by Bond Log.

Halliburton D.V. Packer Collar @ 7230'
Cemented Second Stage W/300 sx. 4% gel.

Baker Model K Packer @ 7281'
23/8" O.D. 4.7# J-55 Tubing
Cisco Perf. 7375 - 7408'
3420. Cisco Perfs. 7474-94
Top Liner 7954'

7" O.D. 23# & 26# N-80 & J-55 Casing Set at 8174'
Cemented First Stage W/100 sx. 20% Diacel "D"

2 3/8", 4.7#, J-55 TUBING w/ SPECIAL OD COUPLINGS

MODEL PL 02/02 w/ PROFILE
3906. BAKER MODEL "A" COLL SET
PKR AT 9210.

Baker Model "D" Packer
@ 9415'

Morrow Perfs. 9544 - 46,
9504 - 00 & 9601 - 04

4 1/2" O.D. 11.8# N-80 Liner
Set @ 9728'
Cemented W/175 sx. Salt Cement.
Cement Circulated Around
Liner.

KERR-MCGEE CORPORATION
MIDLAND, TEXAS

WINSTON - I IN CISCO & MORROW FORMATIONS
2080' FSL. 1980' FWL Section 31, T 21 S - R 24 E
Eddy County, New Mexico