orm 3160-5 une 1990)

CONTINUES STORM APPROVED UNLIED STATES Budget Bureau No. 1004-0135 DEPARTMENT OF THE INTERIOR Expires: March 31, 1993 BUREAU OF LAND MANAGEMENT Lease Designation and Serial No. article. In NM-81218 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE I. Type of Well X Oil Well X Gas Well Other RE-ENTRY 8. Well Name and No. 2. Name of Operator Brannigan ANF Fed. #1 YATES PETROLEUM CORPORATION (505) 748-1471)9. API Well No. 3. Address and Telephone No. 105 South 4th St., Artesia, NM 88210 10. Field and Pool, or Exploratory Area 1. Location of Well (Footage, Sec., T., R., M., or Survey Description) Wildcat Upper Penn 660' FNL & 400' FWL of Section 6-T22S-R24E (Unit D, NWNW) 11. County or Parish, State Eddy Co., NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion New Construction Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection Other Re-entry work (drill Dispose Water (Note: Report results of multiple completion on Well plug, etc.) Completion or Recompletion Report and Log form.) 3. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 9-3-93 - Built location, set and tested anchors and markers. Welded on 9-5/8" X 7" wellhead. Made cut off on 7" casing. 9-4-7-93 - Moved in and rigged up pulling unit. Nippled up tubing head and installed BOP. 9-8-93 - TIH w/bit and 1 drill collar. Tagged cement at 12'. Drilled cement plug #1 from 12' to 120'. TIH w/drill collars and 2-7/8" tubing to 538'. Tagged cement at 538'. Drilled cement plug #2 from 538-710'. Tested BOP to 1500# for 10 minutes, OK. TIH w/2-7/8" tubing to 2351'. Tagged cement retainer at 2351'. Drilled cement retainer. NOTE: Notified Jim Amos w/BLM in Carlsbad of spud time - 8:15 AM 9-7-93. 9-9-93 - TOOH w/2-7/8" tubing, drill collars and bit. TIH w/6-1/8" blade bit, drill collars and tubing to 2381'. Drilled cement from 2381-2411'. TOOH w/tubing, drill collars and blade bit. TIH w/6-1/8" mill tooth bit, drill collars and tubing to 2411'. Drilled cement from 2411-2428'. 9-10-93 - Drilled cement from 2429-2641'. TOOH w/2-7/8'' tubing, drill collars and bit. w/6-1/8" blade bit, drill collars and tubing to 2641'. Drilled cement from 2641-2790'. 9-11-93 - Drilled cement from 2790-3130'. Tested casing to 600 psi for 10 minutes, OK. Washed

and reamed from 3130-5335'. Tagged cement plug #5 at 5335'. Drilled cement from 5335-5460'. CONTINUED ON NEXT PAGE that the foregoing is true and correct Production Clerk Oct. 7, 1993 Title (This space for Federal of State office use) ACCEPTED FOR RECORD Title itle 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfull to any department or agency of the United States any false, fictitious or fraudulent statements representations as to any matter within its jurisdiction.

*See InstruCAR LOS BANDES VALMEXICO