Form 3160-5 (June 1990)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

CHARDY NOTICES AND DEPORTS ON WELLS		NM-81218
Do not use this form for proposals to drill		6. If Indian, Allottee or Tribe Name
	PERMIT—" for such proposals  N TRIPLICATE 05252930	7. If Unit or CA, Agreement Designation
1. Type of Well		<b>"</b>
GOI CAS C		8. Well Name and No.
2. Name of Operator	- /SV NOW NOON	ω Brannigan ANF Federal #1
YATES PETROLEUM CORPORATION	(505) 748-RETAIN	9. API Well No.
3. Address and Telephone No.	O OCD ARTED	30-015-10404
105 South 4th St., Artesia, NM	88210 \(\sigma\)	10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Desc.	ription)	Indian Basin Upper Penn
660' FNL & 400' FWL of Section	6-T22S-R24E (Unit D. ANNIN), ZX	11. County or Parish, State Assoc.
	10000	
		Eddy Co., NM
12. CHECK APPROPRIATE BOX(8)	TO INDICATE NATURE OF NOTICE,	REPORT, OR OTHER DATA S.
TYPE OF SUBMISSION	TYPE OF	ACTION
Notice of Intent	Abandonment	Change of Plans
ACCEPTE OFF	Recompletion	New Construction
X Subsequent Report	Plugging Back	Non-Routine Fracturing
Web of	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	Other Pump acid & sc	
	treatment	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form )
13. Describe Proposed or Completed Operations (Clearly state all p		
11-7-9-98 - Moved in and rigged	depths for all markers and zones pertinent to this work.)*	
11-10-98 - Pumped 75 bbls 2% KC		on vacuum. Ninnlad darm vall
head. Picked up BOP to install		
OCD, BLM, State Police and High		
high winds. Closed section of	Highway 137. Stabbed a 2-7/8"	swedge in 2-7/8" tuhing
Hooked up high pressure 2" hose		
2 BPM at 400 psi. Continued pu		
		& Coots did not want to install
flange and kill well due to dar		
11-11-98 - Picked up wellhead f		
Screwed into 2-7/8" tubing with	subs and wellhead flange. Pi	cked up off slips and pulled
slips away from wellhead. Lowe		
bbls 10# brine water down annul		
	pump. TIH with packer and 2-7	/8" tubing. Set packer at
7347' and tested to 1000 psi.	7/00 700(1 1/1 7500 11	
11-12-98 - Acidized perforation		
with 5 gpt scale inhibitor and		
11-13-98 Pumped 330 gallons 5	<u> </u>	<del></del>
14. I hereby certify that the foregoing latter and correct		TINUED ON NEXT PAGE:
Signed H Justy Jun	Title Operations Technician	n Date Nov. 19, 1998
(This space for Pederal or State office use)		
Approved by	Title	Date
Conditions of approval, if any:		

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

YATES PETROLEUM CORPORATION Brannigan ANF Federal #1 Section 6-T22S-R24E Eddy County, New Mexico

## SUNDRY NOTICE CONTINUED:

into perforations 7420-7896' (Canyon). Unset packer. Installed wellhead and removed BOP. Reset packer at 7367'. Shut well in. 11-14-16-98 - Opened well. Flow testing. Released well to production department.

Rusty Klein

Operations Technician November 19, 1998